

Two modifications for Loidreau's code-based cryptosystem

Wenshuo Guo · Fang-Wei Fu

Received: date / Accepted: date

Abstract This paper presents two modifications for Loidreau's code-based cryptosystem. Loidreau's cryptosystem is a rank metric code-based cryptosystem constructed by using Gabidulin codes in the McEliece setting. Recently a polynomial-time key recovery attack was proposed to break Loidreau's cryptosystem in some cases. To prevent this attack, we propose the use of subcodes to disguise the secret codes in Modification I. In Modification II, we choose a random matrix of low column rank over \mathbb{F}_q to mix with the secret matrix. According to our analysis, these two modifications can both resist the existing structural attacks. Additionally, we adopt the systematic generator matrix of the public code to make a reduction in the public-key size. In addition to stronger resistance against structural attacks and more compact representation of public keys, our modifications also have larger information transmission rates.

Keywords Code-based cryptography · Rank metric codes · Gabidulin codes · Loidreau's cryptosystem

Mathematics Subject Classification (2010) 94B05 · 81Q99

1 Introduction

In 1978, McEliece proposed the first code-based public-key cryptosystem, namely the well-known McEliece cryptosystem based on Goppa codes [1]. Since then cryptologists have made extensive study on its security [2–5]. Apart from some weak keys [6], the McEliece cryptosystem still remains secure in general cases. The main drawback of this cryptosystem lies in its large public-key size, which makes it unpractical in many situations. To overcome this problem, many variants have been

✉ Wenshuo Guo
Chern Institute of Mathematics and LPMC, Nankai University, Tianjin 300071, China
E-mail: ws.guo@mail.nankai.edu.cn

Fang-Wei Fu
Chern Institute of Mathematics and LPMC, Nankai University, Tianjin 300071, China
E-mail: fwfu@nankai.edu.cn

1 proposed. In 1986, Niederreiter [7] introduced a knapsack-type cryptosystem using GRS codes, which was shown to be insecure by Sidelnikov in [8]. But if we
 2 use Goppa codes in the Niederreiter setting, it was proved to be equivalent to
 3 the McEliece cryptosystem in terms of security [9]. GRS codes allow us to reduce
 4 the public-key size due to their optimal error-correcting capability. Many
 5 variants based on GRS codes were proposed after Niederreiter's work. However,
 6 nearly all of these variants were broken one after another because of GRS codes
 7 being highly structured. In the variant [10], the BBCRS cryptosystem, the authors
 8 proposed the use of a dense matrix rather than a permutation matrix to disguise
 9 the structure of the underlying GRS code. In this proposal, the column scrambler
 10 is a matrix of the form $(R + T)^{-1}$, where T is a sparse matrix and R is a dense
 11 matrix of low rank. With this approach, the public code seems quite different from
 12 GRS codes. This variant therefore can resist some known structural attacks, such
 13 as the Sidelnikov-Shestakov attack [8]. However, in [11] the authors presented a
 14 polynomial-time key recovery attack against this variant in some cases. Although
 15 we can adjust the parameters to prevent such an attack, it would bring some other
 16 problems such as the decryption complexity increasing exponentially and a higher
 17 request of error-correcting capability for the underlying code.
 18

19 In 1985 Gabidulin [12] introduced a new family of rank metric codes, known as
 20 the Gabidulin codes. Since the complexity of decoding general rank metric codes is
 21 much higher than that of decoding Hamming metric codes [15, 16], it is feasible to
 22 obtain much smaller public-key sizes by building cryptosystems in the rank metric.
 23 In [17] the authors proposed to use Gabidulin codes in the McEliece setting and
 24 introduced the GPT cryptosystem. Unfortunately, several structural attacks were
 25 put forward to completely break this system [23–25]. To prevent these attacks, variants
 26 based on different masking skills for Gabidulin codes were proposed [18–22].
 27 But in [28] the authors declare the failure of all the previous masking techniques
 28 for Gabidulin codes. In [26] Faure and Loidreau proposed a cryptosystem also
 29 relying on the Gabidulin codes but not in the McEliece setting. Until the work
 30 in [27], the Faure-Loidreau system had never been severely attacked. Recently,
 31 in [29] Loidreau proposed a cryptosystem constructed by using Gabidulin codes in
 32 the McEliece setting. Different from the original GPT cryptosystem, the isometric
 33 matrix is replaced with a matrix whose inverse is taken in an \mathbb{F}_q -subspace of
 34 \mathbb{F}_{q^m} of dimension λ . By doing this, the public code seems quite random. Loidreau
 35 claimed that his proposal could prevent the existing structural attacks. However,
 36 this claim was proved to be invalid by the authors in [30] when $\lambda = 2$ and the
 37 code rate is greater than $1/2$. Soon after this, the author in [31] generalized this
 38 attack to the case of $\lambda > 2$ and the code rate greater than $1 - \frac{1}{\lambda}$. However, it is
 39 feasible to prevent this attack even when the secret code rate is greater than $1 - \frac{1}{\lambda}$
 40 according to our analysis.

41 The rest of this paper is organised as follows. In Section 2 notations and some
 42 concepts about rank metric codes used throughout this paper are given. Section
 43 3 is devoted to a simple description of Loidreau's cryptosystem. In Section 4 we
 44 shall introduce part of the Coggia-Couvreur attack (please refer to [30] for more
 45 details). Following this, our two modifications for Loidreau's cryptosystem will be
 46 introduced in Section 5, then security analysis of our modifications will be given
 47 in Section 6. In Section 7, we will give some suggested parameters for different
 48 security levels and make a comparison with Loidreau's original scheme in Table 1
 49 and with some NIST-PQC submissions in Table 2. Section 8 is our conclusion.

2 Preliminaries

2.1 Notations and basic concepts

Let q be a prime power. Denote by \mathbb{F}_q the finite field with q elements, and \mathbb{F}_{q^m} an extension field of \mathbb{F}_q of degree m . For two positive integers k and n , denote by $\mathcal{M}_{k,n}(\mathbb{F}_{q^m})$ the set of all $k \times n$ matrices over \mathbb{F}_{q^m} , and by $GL_n(\mathbb{F}_{q^m})$ the set of all $n \times n$ invertible matrices over \mathbb{F}_{q^m} . For a matrix $M \in \mathcal{M}_{k,n}(\mathbb{F}_{q^m})$, the column rank of M with respect to \mathbb{F}_q , denoted by $\text{Clr}_q(M)$, is the largest number of columns of M linearly independent over \mathbb{F}_q . Denote by $\langle M \rangle$ the vector space spanned by rows of M over \mathbb{F}_{q^m} .

An $[n, k]$ linear code \mathcal{C} over \mathbb{F}_{q^m} is a k -dimensional subspace of $\mathbb{F}_{q^m}^n$. The dual code of \mathcal{C} , denoted by \mathcal{C}^\perp , is the orthogonal space of \mathcal{C} under the usual Euclidean inner product over \mathbb{F}_{q^m} . A $k \times n$ full-rank matrix $G \in \mathcal{M}_{k,n}(\mathbb{F}_{q^m})$ is called a generator matrix of \mathcal{C} if the vector space $\langle G \rangle$ is exactly the code \mathcal{C} . A generator matrix of \mathcal{C}^\perp is called a parity-check matrix of \mathcal{C} .

2.2 Rank metric codes

Now we recall some basic concepts for rank metric and rank metric codes.

Definition 1 For a vector $\mathbf{x} = (x_1, \dots, x_n) \in \mathbb{F}_{q^m}^n$, the support of \mathbf{x} denoted by $\text{Supp}(\mathbf{x})$, is defined to be the linear space spanned by coordinates of \mathbf{x} over \mathbb{F}_q . Formally we have

$$\text{Supp}(\mathbf{x}) = \left\{ \sum_{i=1}^n \lambda_i x_i : \lambda_i \in \mathbb{F}_q, 1 \leq i \leq n \right\}.$$

Definition 2 For a vector $\mathbf{x} \in \mathbb{F}_{q^m}^n$, the rank weight of \mathbf{x} denoted by $w_R(\mathbf{x})$, is defined to be the dimension of $\text{Supp}(\mathbf{x})$ over \mathbb{F}_q .

Given two vectors $\mathbf{x}, \mathbf{y} \in \mathbb{F}_{q^m}^n$, the rank distance between \mathbf{x} and \mathbf{y} , denoted by $d_R(\mathbf{x}, \mathbf{y})$, is defined to be the rank weight of $\mathbf{x} - \mathbf{y}$. It is easy to verify that the function $d_R(\cdot, \cdot)$ defines a proper metric on $\mathbb{F}_{q^m}^n$. A code endowed with the rank metric is called a rank metric code, and in this paper by rank metric codes we always mean linear rank metric codes.

Definition 3 For a rank metric code $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$, the minimum rank distance of \mathcal{C} , denoted by $d(\mathcal{C})$, is defined as

$$d(\mathcal{C}) = \min\{d_R(\mathbf{x}, \mathbf{y}) : \mathbf{x}, \mathbf{y} \in \mathcal{C} \text{ and } \mathbf{x} \neq \mathbf{y}\}.$$

It is easy to verify that the minimum rank (Hamming) distance of a linear code is equal to its minimum rank (Hamming) weight. In the context of Hamming metric codes, the minimum distance d of an $[n, k]$ linear code satisfies the Singleton bound $d \leq n - k + 1$ [32]. Similarly, the minimum rank distance of a rank metric code \mathcal{C} satisfies the following Singleton-style bound.

1 **Theorem 1 (Singleton-style bound)** [33] Let $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$ be an $[n, k]$ rank metric
 2 code, then the minimum rank distance of \mathcal{C} with respect to \mathbb{F}_q satisfies the following
 3 inequality

$$d(\mathcal{C}) \leq n - k + 1.$$

4 *Remark 1* A linear code attaining the Singleton-style bound is called a Maximum
 5 Rank Distance (MRD) code. Apparently an $[n, k]$ MRD code can correct up to
 6 $\lfloor \frac{n-k}{2} \rfloor$ rank errors.

7 The following proposition implies that the maximum rank weight of a rank
 8 metric code is bounded from above by the column rank of its generator matrix.

9 **Proposition 1** For a matrix $M \in \mathcal{M}_{k,n}(\mathbb{F}_{q^m})$ with $\text{Clr}_q(M) = r$, the maximum
 10 rank weight of the code $\langle M \rangle$ is bounded by r from above.

11 *Proof* It suffices to prove that for any $\mathbf{v} \in \langle M \rangle$, we have $w_R(\mathbf{v}) \leq r$. Since
 12 $\text{Clr}_q(M) = r$, there exists $Q \in GL_n(\mathbb{F}_q)$ such that $MQ = [M'|O]$, where $M' \in$
 13 $\mathcal{M}_{k,r}(\mathbb{F}_{q^m})$ with $\text{Clr}_q(M') = r$ and O is a zero matrix. For any $\mathbf{v} \in \langle M \rangle$, there
 14 exists $\mathbf{x} \in \mathbb{F}_{q^m}^k$ such that $\mathbf{v} = \mathbf{x}M$ and

$$\mathbf{v}Q = \mathbf{x}MQ = \mathbf{x}[M'|O] = (\mathbf{x}', \mathbf{0}),$$

15 where $\mathbf{x}' \in \mathbb{F}_{q^m}^r$ and $\mathbf{0}$ is a zero vector. Hence we have $w_R(\mathbf{v}) = w_R(\mathbf{v}Q) \leq r$. This
 16 concludes the proof.

17 2.3 Gabidulin codes

18 Gabidulin codes can be viewed as an analogue of GRS codes in the rank metric
 19 setting, and these two types of codes resemble each other closely in the construction
 20 principle. GRS codes admit generator matrices with the Vandermonde structure,
 21 while Gabidulin codes can be described by Moore matrices defined as follows.

Definition 4 For an integer s , denote by $[s]$ the s -th Frobenius power q^s . A
 matrix $G \in \mathcal{M}_{k,n}(\mathbb{F}_{q^m})$ is called a Moore matrix generated by $\mathbf{a} = (a_1, \dots, a_n) \in$
 $\mathbb{F}_{q^m}^n$ if the s -th row of G equals the coordinate-wise Frobenius power $\mathbf{a}^{[s-1]} =$
 $(a_1^{[s-1]}, \dots, a_n^{[s-1]})$ for each $1 \leq s \leq k$. Formally we have

$$G = \begin{pmatrix} a_1 & a_2 & \cdots & a_n \\ a_1^{[1]} & a_2^{[1]} & \cdots & a_n^{[1]} \\ \vdots & \vdots & & \vdots \\ a_1^{[k-1]} & a_2^{[k-1]} & \cdots & a_n^{[k-1]} \end{pmatrix}. \quad (1)$$

22 For a matrix $G \in \mathcal{M}_{k,n}(\mathbb{F}_{q^m})$, we define $G^{[s]} = (G_{ij}^{[s]})$. For a set $S \subseteq \mathbb{F}_{q^m}^n$, we
 23 define $S^{[s]} = \{\mathbf{x}^{[s]} : \mathbf{x} \in S\}$. For a linear code $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$, it is easy to verify that
 24 $\mathcal{C}^{[s]}$ is also an \mathbb{F}_{q^m} -linear code.

25 **Definition 5 (Gabidulin codes)** For a vector $\mathbf{a} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{a}) = n \leq m$,
 26 let G be the $k \times n$ Moore matrix generated by \mathbf{a} . The $[n, k]$ Gabidulin code $\mathcal{G}_{n,k}(\mathbf{a})$
 27 over \mathbb{F}_{q^m} generated by \mathbf{a} is defined to be the linear space $\langle G \rangle$, namely we have
 28 $\mathcal{G}_{n,k}(\mathbf{a}) = \langle G \rangle$.

1 A major reason for Gabidulin codes being widely used in the design of cryp-
 2 tosystems consists in their remarkable error-correcting capability and simple al-
 3 gebraic structure. Now we recall some properties of Gabidulin codes through the
 4 following two theorems without proving.

5 **Theorem 2** [34] *The Gabidulin code $\mathcal{G}_{n,k}(\mathbf{a})$ is an MRD code. In other words,*
 6 *$\mathcal{G}_{n,k}(\mathbf{a})$ attains the Singleton-style bound for rank metric codes.*

7 According to Theorem 2, the minimum rank distance of $\mathcal{G}_{n,k}(\mathbf{a})$ is $n - k + 1$.
 8 This implies that any $\lfloor \frac{n-k}{2} \rfloor$ rank errors can be corrected. In fact, several efficient
 9 decoding algorithms for Gabidulin codes already exist (for instance [12–14]).

10 **Theorem 3** [27] *The dual code of $\mathcal{G}_{n,k}(\mathbf{a})$ is the Gabidulin code $\mathcal{G}_{n,n-k}(\mathbf{b}^{\lfloor k-n+1 \rfloor})$*
 11 *for some $\mathbf{b} \in \mathcal{G}_{n,n-1}(\mathbf{a})^\perp$ with $w_R(\mathbf{b}) = n$.*

12 3 Loidreau's scheme

13 For a vector $\mathbf{a} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{a}) = n$, denote by G a generator matrix of $\mathcal{G}_{n,k}(\mathbf{a})$.
 14 For a positive integer $\lambda \ll m$, let $\mathcal{V} \subseteq \mathbb{F}_{q^m}$ be an \mathbb{F}_q -linear space of dimension λ .
 15 Now we give a simple description of Loidreau's scheme through the following three
 16 algorithms.

17 – Key Generation

18 Randomly choose $P \in GL_n(\mathbb{F}_{q^m})$ whose entries are taken from \mathcal{V} and compute
 19 $G_{pub} = GP^{-1}$. We publish (G_{pub}, t) as the public key where $t = \lfloor \frac{n-k}{2\lambda} \rfloor$, and
 20 keep (\mathbf{a}, P) as the secret key.

21 – Encryption

22 For a plaintext $\mathbf{m} \in \mathbb{F}_{q^m}^k$, randomly choose a vector $\mathbf{e} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{e}) = t$.
 23 The ciphertext corresponding to \mathbf{m} is computed as $\mathbf{c} = \mathbf{m}G_{pub} + \mathbf{e}$.

24 – Decryption

25 Compute $\mathbf{c}' = \mathbf{c}P = \mathbf{m}G + \mathbf{e}P$. Since $w_R(\mathbf{e}P) \leq w_R(\mathbf{e}) \cdot \dim_q(\mathcal{V}) \leq \lfloor \frac{n-k}{2} \rfloor$,
 26 decoding \mathbf{c}' will lead to the plaintext \mathbf{m} .

27 4 The Coggia-Couvreur attack

28 Before describing the Coggia-Couvreur attack, we first introduce a distinguisher
 29 for Gabidulin codes. This distinguisher provides us with a method of distinguishing
 30 Gabidulin codes from general ones.

31 4.1 The distinguisher for Gabidulin codes

32 Most of cryptosystems based on Gabidulin codes have been proved to be insecure
 33 against structural attacks. Although these attacks were proposed to cryptanalyze
 34 different variants of the GPT cryptosystem, the principle for their work is based
 35 on the same observation that one can distinguish Gabidulin codes from general
 36 ones by performing a simple operation on these codes.

37 Given a random linear code $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$ of dimension $k \leq n/2$, the expected
 38 dimension of the code $\mathcal{C} + \mathcal{C}^{[1]}$ equals $2k$, or equivalently $\mathcal{C} \cap \mathcal{C}^{[1]} = \{\mathbf{0}\}$ holds with

high probability. But for a Gabidulin code $\mathcal{G}_{n,k}(\mathbf{a})$, we have $\mathcal{G}_{n,k}(\mathbf{a}) + \mathcal{G}_{n,k}(\mathbf{a})^{[1]} = \mathcal{G}_{n,k+1}(\mathbf{a})$, namely the dimension of $\mathcal{G}_{n,k}(\mathbf{a}) + \mathcal{G}_{n,k}(\mathbf{a})^{[1]}$ is $k+1$. More generally, we have the following two propositions.

Proposition 2 [30] *Let $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$ be a random linear code of length n and dimension k . For a non-negative integer l and a positive integer $s < k$, we have*

$$\Pr\left(\dim(\mathcal{C} + \mathcal{C}^{[1]} + \cdots + \mathcal{C}^{[s]}) \leq \min\{n, (s+1)k\} - l\right) = O(q^{-ml}).$$

Proposition 3 [30] *Let $k \leq n$ and s be a positive integer, then for any $\mathbf{a} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{a}) = n$, we have*

$$\begin{aligned} \mathcal{G}_{n,k}(\mathbf{a}) \cap \mathcal{G}_{n,k}(\mathbf{a})^{[1]} &= \mathcal{G}_{n,k-1}(\mathbf{a}^{[1]}); \\ \mathcal{G}_{n,k}(\mathbf{a}) + \mathcal{G}_{n,k}(\mathbf{a})^{[1]} + \cdots + \mathcal{G}_{n,k}(\mathbf{a})^{[s]} &= \mathcal{G}_{n,k+s}(\mathbf{a}). \end{aligned}$$

4.2 Description of the Coggia-Couvreur attack

In this part we investigate the structural vulnerability of Loidreau's cryptosystem in the case of $\lambda = 2$ and the dimension of the public code $\mathcal{C}_{pub} = \langle G_{pub} \rangle$ being greater than $n/2$. The principle for the Coggia-Couvreur attack lies in Propositions 2 and 3. Instead of directly operating the public code, the authors in [30] consider the dual of the public code because of the following lemma.

Lemma 1 [30] *Any parity-check matrix H_{pub} of \mathcal{C}_{pub} can be expressed as*

$$H_{pub} = H_{sec} P^T,$$

where H_{sec} is a parity-check matrix of the secret Gabidulin code $\mathcal{G}_{n,k}(\mathbf{a})$.

The authors considered the case of $\lambda = 2$, namely the linear space $\mathcal{V} \subseteq \mathbb{F}_{q^m}$ has dimension 2 over \mathbb{F}_q . Suppose \mathcal{V} is spanned by $\alpha, \beta \in \mathbb{F}_{q^m}^*$ over \mathbb{F}_q , namely $\mathcal{V} = \langle \alpha, \beta \rangle_{\mathbb{F}_q}$. Let $H'_{sec} = \alpha H_{sec}$ and $P' = \alpha^{-1} P$, apparently we have $H_{pub} = H'_{sec} P'^T$. It is easy to see that H'_{sec} spans the same code as H_{sec} and entries of P' are contained in $\mathcal{V}' = \langle 1, \alpha^{-1} \beta \rangle_{\mathbb{F}_q}$. Hence it is reasonable to suppose that $\mathcal{V} = \langle 1, \gamma \rangle_{\mathbb{F}_q}$ for some $\gamma \in \mathbb{F}_{q^m}^*$. In this situation, we can express P^T in the form of

$$P^T = P_0 + \gamma P_1,$$

where $P_0, P_1 \in \mathcal{M}_{n,n}(\mathbb{F}_q)$.

According to Theorem 3, there exists some $\mathbf{b} \in \mathcal{G}_{n,n-1}(\mathbf{a})^\perp$ with $w_R(\mathbf{b}) = n$ such that $\mathcal{G}_{n,k}(\mathbf{a})^\perp = \mathcal{G}_{n,n-k}(\mathbf{b})$. We define

$$\mathbf{g} = \mathbf{b}P_0, \mathbf{h} = \mathbf{b}P_1.$$

As for the triple $(\gamma, \mathbf{g}, \mathbf{h})$, the authors made the following two assumptions:

- (1) $\mathcal{G}_{n,n-k+2}(\mathbf{g}) \cap \mathcal{G}_{n,n-k+2}(\mathbf{h}) = \{\mathbf{0}\}$ and $w_R(\mathbf{g}), w_R(\mathbf{h}) \geq n - k + 2$;
- (2) $m > 2$ and γ is not contained in any proper subfield of \mathbb{F}_{q^m} .

1 The rationality for these two assumptions can be explained as follows. Ac-
 2 cording to the authors' experiments on Magma, Assumption (1) holds with an
 3 extremely high probability. Apparently $m > 2$ is reasonable because of $m \geq n$. On
 4 the other hand, if γ is contained in some proper subfield of \mathbb{F}_{q^m} , then the adversary
 5 can find γ through the exhausting method for the reason that even the union of
 6 all proper subfields of \mathbb{F}_{q^m} contains much less elements than \mathbb{F}_{q^m} . Hence γ cannot
 7 be contained in any proper subfield of \mathbb{F}_{q^m} .

8 The core of the Coggia-Couvreur attack is to find the triple $(\gamma, \mathbf{g}, \mathbf{h})$ or one of
 9 its equivalent forms (see [30] for more details). With the knowledge of the triple
 10 $(\gamma, \mathbf{g}, \mathbf{h})$ or one of its equivalent forms, one can decrypt any valid ciphertext in
 11 polynomial time and hence completely break Loidreau's cryptosystem.

12 What follows are two lemmas that will be useful for analysing the security of our
 13 modifications. For the remaining part of the Coggia-Couvreur attack, interested
 14 readers can refer to [30] for more details. Now we introduce these two lemmas
 15 without proving.

Lemma 2 [30] *The code \mathcal{C}_{pub}^\perp is spanned by*

$$\mathbf{g} + \gamma \mathbf{h}, \mathbf{g}^{[1]} + \gamma \mathbf{h}^{[1]}, \dots, \mathbf{g}^{[n-k-1]} + \gamma \mathbf{h}^{[n-k-1]}. \quad (2)$$

16 **Lemma 3** [30] *Under Assumption (1), we have that $\mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}$ is spanned by*

$$\mathbf{g} + \gamma \mathbf{h} \text{ and } \mathbf{g}^{[1]}, \mathbf{h}^{[1]}, \dots, \mathbf{g}^{[n-k-1]}, \mathbf{h}^{[n-k-1]} \text{ and } \mathbf{g}^{[n-k]} + \gamma^{[1]} \mathbf{h}^{[n-k]},$$

17 *and*

$$(\mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}) \cap (\mathcal{C}_{pub}^{\perp [1]} + \mathcal{C}_{pub}^{\perp [2]})$$

18 *is spanned by*

$$\mathbf{g}^{[1]} + \gamma^{[1]} \mathbf{h}^{[1]} \text{ and } \mathbf{g}^{[2]}, \mathbf{h}^{[2]}, \dots, \mathbf{g}^{[n-k-1]}, \mathbf{h}^{[n-k-1]} \text{ and } \mathbf{g}^{[n-k]} + \gamma^{[1]} \mathbf{h}^{[n-k]}.$$

Remark 2 Similar to Lemma 3, it is easy to verify that

$$(\mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}) \cap (\mathcal{C}_{pub}^{\perp [1]} + \mathcal{C}_{pub}^{\perp [2]}) \cap \dots \cap (\mathcal{C}_{pub}^{\perp [n-k-1]} + \mathcal{C}_{pub}^{\perp [n-k]}) \quad (3)$$

yields a code spanned by

$$\mathbf{g}^{[n-k-1]} + \gamma^{[n-k-1]} \mathbf{h}^{[n-k-1]} \text{ and } \mathbf{g}^{[n-k]} + \gamma^{[1]} \mathbf{h}^{[n-k]}. \quad (4)$$

19 The key point for the Coggia-Couvreur attack is that one can obtain (4) by
 20 computing (3). But if $\mathcal{C}_{pub}^{\perp [i]} + \mathcal{C}_{pub}^{\perp [i+1]}$ ($0 \leq i \leq n - k - 1$) happens to be the
 21 whole space $\mathbb{F}_{q^m}^n$, computing (4) will lead to nothing but the whole space itself,
 22 which means that the Coggia-Couvreur attack will fail in this situation. Our first
 23 modification for Loidreau's cryptosystem is inspired by this observation. On the
 24 other hand, if \mathcal{C}_{pub}^\perp does not contain the full code spanned by (2), then one cannot
 25 obtain (4) from (3) either even if $\mathcal{C}_{pub}^{\perp [i]} + \mathcal{C}_{pub}^{\perp [i+1]}$ ($0 \leq i \leq n - k - 1$) is not the
 26 whole space. Modification II is based on this observation and this is really true
 27 according to our analysis in Section 6.

5 Our modifications

In code-based cryptography, randomness is widely used in both the key generation and encryption procedures. In terms of the intersection of a given linear code and a randomly chosen linear space, we have the following proposition.

Proposition 4 *Let n, k, l be positive integers with $k + l < n$. Let $\mathcal{C} \subseteq \mathbb{F}_q^n$ be a linear code of dimension k , and \mathcal{V} be a random linear subspace of \mathbb{F}_q^n of dimension l . In terms of the intersection $\mathcal{C} \cap \mathcal{V}$, we have the following inequality*

$$\Pr\{\mathcal{C} \cap \mathcal{V} = \{\mathbf{0}\}\} \geq 1 - O(q^{-ms}),$$

where $s \geq 2$ is a positive integer.

Proof Exploiting the Gaussian coefficient, the number of l -dimensional subspaces of \mathbb{F}_q^n linearly independent of \mathcal{C} can be computed as

$$N_1 = \prod_{i=0}^{l-1} \frac{(q^m)^n - (q^m)^{k+i}}{(q^m)^l - (q^m)^i} = \prod_{i=0}^{l-1} \frac{q^{mn} - q^{m(k+i)}}{q^{ml} - q^{mi}}.$$

Similarly, the number of all l -dimensional subspaces of \mathbb{F}_q^n can be computed as

$$N_2 = \prod_{i=0}^{l-1} \frac{(q^m)^n - (q^m)^i}{(q^m)^l - (q^m)^i} = \prod_{i=0}^{l-1} \frac{q^{mn} - q^{mi}}{q^{ml} - q^{mi}}.$$

Then the target probability $\Pr\{\mathcal{C} \cap \mathcal{V} = \{\mathbf{0}\}\}$ can be computed as

$$\begin{aligned} \frac{N_1}{N_2} &= \prod_{i=0}^{l-1} \frac{q^{mn} - q^{m(k+i)}}{q^{mn} - q^{mi}} \\ &= \prod_{i=0}^{l-1} \frac{q^{mn} - q^{mi} - q^{mk+mi} + q^{mi}}{q^{mn} - q^{mi}} \\ &= \prod_{i=0}^{l-1} \left(1 - \frac{q^{mk} - 1}{q^{m(n-i)} - 1}\right) \\ &\geq \left(1 - \frac{q^{mk} - 1}{q^{m(n-l+1)} - 1}\right)^l. \end{aligned} \tag{5}$$

By Taylor expansion, the right hand side of (5) can be expressed as

$$\begin{aligned} \left(1 - \frac{q^{mk} - 1}{q^{m(n-l+1)} - 1}\right)^l &= 1 - l \cdot \frac{q^{mk} - 1}{q^{m(n-l+1)} - 1} + o\left(\frac{q^{mk} - 1}{q^{m(n-l+1)} - 1}\right) \\ &= 1 - O\left(q^{-m(n-k-l+1)}\right). \end{aligned}$$

Let $s = n - k - l + 1$, apparently $s \geq 2$ because of $k + l < n$. Finally we have $\Pr\{\mathcal{C} \cap \mathcal{V} = \{\mathbf{0}\}\} \geq 1 - O(q^{-ms})$. This completes the proof.

Remark 3 Proposition 4 states a fact that for a linear code \mathcal{C} and a randomly chosen linear space \mathcal{V} , we have that $\mathcal{C} \cap \mathcal{V} = \{\mathbf{0}\}$ holds with high probability. Meanwhile, it is reasonable to conclude that for a $k \times n$ full-rank matrix H and a randomly chosen $l \times n$ full-rank matrix A with $k + l < n$, the block matrix $\begin{pmatrix} A \\ H \end{pmatrix}$ is of full rank with high probability.

5.1 Description of Modification I

Let \mathcal{G} be an $[n, k]$ Gabidulin code generated by $\mathbf{a} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{a}) = n$. Denote by H a parity-check matrix of \mathcal{G} . For a positive integer $l \geq k - \frac{n}{2}$, randomly choose an $l \times n$ full-rank matrix A over \mathbb{F}_{q^m} and set $H_{sub} = \begin{pmatrix} A \\ H \end{pmatrix}$. Let G_{sub} be a generator matrix of $\langle H_{sub} \rangle^\perp$. By Proposition 4, H_{sub} has rank $k + l$ with high probability. It would be well if we assume that H_{sub} is of full rank, otherwise we rechoose the matrix A . Apparently G_{sub} spans a subcode of \mathcal{G} of dimension $k' = k - l$. For a positive integer $\lambda \ll m$, let $\mathcal{V} \subseteq \mathbb{F}_{q^m}$ be an \mathbb{F}_q -linear space of dimension λ .

– Key generation

Let $P \in GL_n(\mathbb{F}_{q^m})$ with entries contained in \mathcal{V} . Without loss of generality, we assume that the submatrix of $G_{sub}P^{-1}$ formed by the first k' columns is invertible. Choose a matrix $S \in GL_{k'}(\mathbb{F}_{q^m})$ to change $G_{pub} = SG_{sub}P^{-1}$ into systematic form. We publish (G_{pub}, t) as the public key where $t = \lfloor \frac{n-k}{2\lambda} \rfloor$, and keep (\mathbf{a}, P) as the secret key.

– Encryption

For a plaintext $\mathbf{m} \in \mathbb{F}_{q^m}^{k'}$, randomly choose $\mathbf{e} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{e}) = t$. Then the ciphertext corresponding to \mathbf{m} is computed as $\mathbf{c} = \mathbf{m}G_{pub} + \mathbf{e}$.

– Decryption

For a ciphertext \mathbf{c} , compute $\mathbf{c}' = \mathbf{c}P = \mathbf{m}SG_{sub} + \mathbf{e}P$. Since $w_R(\mathbf{e}P) \leq w_R(\mathbf{e}) \cdot \lambda \leq \lfloor \frac{n-k}{2} \rfloor$. Applying the decoding procedure of \mathcal{G} to \mathbf{c}' will lead to $\mathbf{e}' = \mathbf{e}P$, then we have $\mathbf{e} = \mathbf{e}'P^{-1}$. The restriction of $\mathbf{c} - \mathbf{e}$ to the first k' coordinates will be the plaintext \mathbf{m} .

Remark 4 According to the analysis in Section 4.2, we can always assume that $1 \in \mathcal{V}$. If $\lambda = 1$, there will be $\mathcal{V} = \mathbb{F}_q$ and $P^{-1} \in GL_n(\mathbb{F}_q)$. In this situation, G_{pub} spans a subcode of \mathcal{G} . Then one can exploit the r -Frobenius weak attack [35] to completely break this modification. To prevent this attack, we should make sure that $\lambda \geq 2$ in Modification I.

5.2 Description of Modification II

Let \mathcal{G} be an $[n, k]$ Gabidulin code generated by $\mathbf{a} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{a}) = n$. Denote by G a generator matrix of \mathcal{G} . For a positive integer $l \ll \min\{k, n - k\}$, randomly choose $M \in \mathcal{M}_{k,n}(\mathbb{F}_{q^m})$ with $\text{Clr}_q(M) = l$ and let $G_M = G + M$. It is easy to see that G_M is of full rank. Indeed, if there exists $\mathbf{x} \in \mathbb{F}_{q^m}^k$ such that $\mathbf{x}G_M = \mathbf{0}$, then we have $\mathbf{x}G \in \langle M \rangle$. By Proposition 1, the maximum rank weight of $\langle M \rangle$ does not exceed l . Together with $d(\mathcal{G}) = n - k + 1 \gg l$, we have $\mathbf{x}G = \mathbf{0}$ and hence $\mathbf{x} = \mathbf{0}$. For a positive integer $\lambda \ll m$, let $\mathcal{V} \subseteq \mathbb{F}_{q^m}$ be an \mathbb{F}_q -linear space of dimension λ .

– Key generation

Let $P \in GL_n(\mathbb{F}_{q^m})$ with entries contained in \mathcal{V} . Without loss of generality, we assume that the submatrix of G_MP^{-1} formed by the first k columns is invertible. Choose a matrix $S \in GL_k(\mathbb{F}_{q^m})$ to change $G_{pub} = SG_MP^{-1}$ into systematic form. We publish (G_{pub}, t) as the public key where $t = \lfloor \frac{n-k-2l}{2\lambda} \rfloor$, and keep (S, G, P) as the secret key.

– Encryption

- 1 For a plaintext $\mathbf{m} \in \mathbb{F}_{q^m}^k$, randomly choose a vector $\mathbf{e} \in \mathbb{F}_{q^m}^n$ with $w_R(\mathbf{e}) = t$.
 2 Then the ciphertext corresponding to \mathbf{m} is computed as $\mathbf{c} = \mathbf{m}G_{pub} + \mathbf{e}$.
 3 – Decryption
 For a ciphertext \mathbf{c} , compute $\mathbf{c}' = \mathbf{c}P = \mathbf{m}SG + \mathbf{m}SM + \mathbf{e}P$. Since

$$w_R(\mathbf{m}SM + \mathbf{e}P) \leq w_R(\mathbf{m}SM) + w_R(\mathbf{e}P) \leq l + \lambda t \leq \lfloor \frac{n-k}{2} \rfloor,$$

- 4 applying the decoding procedure of \mathcal{G} to \mathbf{c}' will lead to $\mathbf{m}SG$. Then the plain-
 5 text \mathbf{m} can be recovered by solving a linear system with a complexity of $O(n^3)$.

- 6 *Remark 5* Similar to the analysis in Remark 4, we should make sure that $\lambda \geq$
 7 2 in this modification. Otherwise, Modification II can be reduced to the GPT
 8 cryptosystem that has been completely broken.

9 6 Security analysis

- 10 In general, there are two types of attacks on code-based cryptosystems, namely
 11 the generic attack and structural attack.

- 12 **Generic attacks.** These attacks aim to recover the plaintext directly from the
 13 ciphertext when nothing but the public key is known. In the context of code-based
 14 cryptography, generic attacks are involved with the problem of decoding general
 15 linear codes or equivalently the syndrome decoding problem, both of which are
 16 believed to be very difficult by the community. In the paper [36], the authors
 17 proposed two generic attacks on the rank syndrome decoding (RSD) problem,
 18 which lay a foundation for the security of rank metric code-based cryptography.

- 19 Suppose \mathcal{C} is an $[n, k]$ rank metric code over \mathbb{F}_{q^m} , correcting up to t rank errors.
 20 Let $\mathbf{y} = \mathbf{c} + \mathbf{e}$, where \mathbf{c} is a codeword in \mathcal{C} and \mathbf{e} is a random vector with $w_R(\mathbf{e}) = t$.
 21 The first attack in [36] is combinatorial and permits to recover the error \mathbf{e} with

$$\min\{O((n-k)^3 m^3 q^{t \lfloor (km)/n \rfloor}), O((n-k)^3 m^3 q^{(t-1) \lfloor ((k+1)m)/n \rfloor})\}$$

- 22 operations in \mathbb{F}_q . The second attack in [36] is algebraic and shows that in the case
 23 of $\lceil ((t+1)(k+1) - (n+1))/t \rceil \leq k$, the RSD problem can be solved with an
 24 average complexity of

$$O(t^3 k^3 q^{t \lceil ((t+1)(k+1) - (n+1))/t \rceil})$$

- 25 in \mathbb{F}_q . Apparently both of these two attacks need exponential time to recover the
 26 plaintext without knowing the secret key.

- 27 **Structural attacks.** These attacks aim to recover the structure of the se-
 28 cret code from a random-looking public matrix. In fact, recovering the structure
 29 amounts to obtaining the secret key in some sense, which means that the cryptosys-
 30 tem will be completely broken in this situation. In [29], Loidreau argued that his
 31 cryptosystem could resist the invariant subspace attack, also known as Overbeck's
 32 attack. Since our modifications exploit the same masking technique to disguise the
 33 structure of the secret code, naturally we believe that our modifications can also
 34 prevent Overbeck's attack. Therefore, in the remaining part of this section we only
 35 consider the security against the Coggia-Couvreur attack.

6.1 Analysis of Modification I

Before giving the analysis, we shall introduce the following theorem. This theorem states a simple fact that if $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$ is a linear code with a generator matrix G , then its s -th Frobenius power $\mathcal{C}^{[s]}$ is also a linear code over \mathbb{F}_{q^m} and has $G^{[s]}$ as a generator matrix.

Theorem 4 *Let $\mathcal{C} \subseteq \mathbb{F}_{q^m}^n$ be an $[n, k]$ linear code that has G as a generator matrix. For any integer s , $\mathcal{C}^{[s]}$ is also an $[n, k]$ linear code over \mathbb{F}_{q^m} and has $G^{[s]}$ as a generator matrix.*

Proof On the one hand. For any $\mathbf{u} \in \mathcal{C}^{[s]}$, there exists $\mathbf{x} \in \mathbb{F}_{q^m}^k$ such that $\mathbf{u} = (\mathbf{x}G)^{[s]} = \mathbf{x}^{[s]}G^{[s]} \in \langle G^{[s]} \rangle$, then we have

$$\mathcal{C}^{[s]} \subseteq \langle G^{[s]} \rangle.$$

On the other hand. For any $\mathbf{v} \in \langle G^{[s]} \rangle$, there exists $\mathbf{x} \in \mathbb{F}_{q^m}^k$ such that $\mathbf{v} = \mathbf{x}G^{[s]} = (\mathbf{x}^{[m-s]}G)^{[s]} \in \mathcal{C}^{[s]}$, then we have

$$\langle G^{[s]} \rangle \subseteq \mathcal{C}^{[s]}.$$

Hence we have $\mathcal{C}^{[s]} = \langle G^{[s]} \rangle$.

It remains to prove that $G^{[s]}$ is of full rank. Suppose there exists $\mathbf{x} \in \mathbb{F}_{q^m}^k$ such that $\mathbf{x}G^{[s]} = (\mathbf{x}^{[m-s]}G)^{[s]} = \mathbf{0}$, then we have $\mathbf{x}^{[m-s]}G = \mathbf{0}$ and consequently $\mathbf{x} = \mathbf{x}^{[m-s]} = \mathbf{0}$ because of G being of full rank. This concludes the proof.

Now we show that $\mathcal{C}_{pub}^{\perp [i]} + \mathcal{C}_{pub}^{\perp [i+1]}$ ($0 \leq i \leq n - k - 1$) is exactly the whole space $\mathbb{F}_{q^m}^n$, namely all these $n - k$ codes have dimension n . By Theorem 4, it suffices to consider the case of $\mathcal{C}_{pub}^{\perp [1]} + \mathcal{C}_{pub}^{\perp [1]}$.

Let H_{pub} be a parity-check matrix of \mathcal{C}_{pub} , then we have $H_{pub} = H_{sub}P^T$ and

$$\mathcal{C}_{pub}^{\perp [1]} = \langle H_{sub}P^T \rangle = \langle HP^T \rangle + \langle AP^T \rangle.$$

Hence

$$\mathcal{C}_{pub}^{\perp [1]} + \mathcal{C}_{pub}^{\perp [1]} = \langle HP^T \rangle + \langle HP^T \rangle^{[1]} + \langle AP^T \rangle + \langle AP^T \rangle^{[1]}.$$

According to Lemma 3, $\langle HP^T \rangle + \langle HP^T \rangle^{[1]}$ is spanned by

$$\mathbf{g} + \gamma\mathbf{h} \text{ and } \mathbf{g}^{[1]}, \mathbf{h}^{[1]}, \dots, \mathbf{g}^{[n-k-1]}, \mathbf{h}^{[n-k-1]} \text{ and } \mathbf{g}^{[n-k]} + \gamma^{[1]}\mathbf{h}^{[n-k]}, \quad (6)$$

where γ, \mathbf{g} and \mathbf{h} are defined as in Section 4.

Note that these $2(n - k)$ vectors in (6) are linearly independent over \mathbb{F}_{q^m} .

Indeed, if there exist $x_i, y_i \in \mathbb{F}_{q^m}$ ($0 \leq i \leq n - k - 1$) such that

$$x_0(\mathbf{g} + \gamma\mathbf{h}) + y_0(\mathbf{g}^{[n-k]} + \gamma^{[1]}\mathbf{h}^{[n-k]}) + \sum_{i=1}^{n-k-1} x_i\mathbf{g}^{[i]} + \sum_{i=1}^{n-k-1} y_i\mathbf{h}^{[i]} = \mathbf{0}.$$

Then we have

$$y_0\mathbf{g}^{[n-k]} + \sum_{i=0}^{n-k-1} x_i\mathbf{g}^{[i]} = -x_0\gamma\mathbf{h} - y_0\gamma^{[1]}\mathbf{h}^{[n-k]} - \sum_{i=1}^{n-k-1} y_i\mathbf{h}^{[i]}.$$

1 Apparently $y_0 \mathbf{g}^{[n-k]} + \sum_{i=0}^{n-k-1} x_i \mathbf{g}^{[i]} \in \mathcal{G}_{n,n-k+2}(\mathbf{g})$ and $-x_0 \gamma \mathbf{h} - y_0 \gamma^{[1]} \mathbf{h}^{[n-k]} -$
 2 $\sum_{i=1}^{n-k-1} y_i \mathbf{h}^{[i]} \in \mathcal{G}_{n,n-k+2}(\mathbf{h})$. Hence $x_i = y_i = 0$ ($0 \leq i \leq n-k-1$) because of
 3 Assumption (1).

4 By Proposition 2, we have that $\dim(\langle AP^T \rangle + \langle AP^T \rangle^{[1]}) = 2l$ holds with ex-
 5 tremely high probability. Together with Proposition 4, we have that $\dim(\mathcal{C}_{pub}^\perp +$
 6 $\mathcal{C}_{pub}^{\perp [1]}) = n = \min\{2(n-k+l), n\}$. This means that by computing the inter-
 7 section (3) the adversary can obtain nothing but the whole space and hence the
 8 Coggia-Couvreur attack will fail in this situation.

9 6.2 Analysis of Modification II

10 Since $\text{Clr}_q(M) = l$, there must be $1 \leq \text{Rank}(M) \leq l$. Assume that $\text{Rank}(M) = l'$,
 11 apparently we have $\dim(\langle M \rangle) = l' \leq l$. By Proposition 1, we have $w_R(\mathbf{v}) \leq l$ for
 12 any $\mathbf{v} \in \langle M \rangle$. Together with $d(\mathcal{G}) = n-k+1 \gg l$, we have $\langle M \rangle \cap \mathcal{G} = \{\mathbf{0}\}$.

13 Let $\mathcal{C}_{pub} = \langle G_{pub} \rangle = \langle SG_M P^{-1} \rangle$, then a parity-check matrix for \mathcal{C}_{pub} can be
 14 written as $H_{pub} = H_M P^T$, where H_M is an $(n-k) \times n$ full-rank matrix such that
 15 $SG_M H_M^T = \mathbf{0}$. It is easy to see that $\langle H_M \rangle$ contains a subcode of \mathcal{G}^\perp of dimension
 16 $n-k-l'$. Hence \mathcal{C}_{pub}^\perp contains a subcode of \mathcal{C}_1 of dimension $n-k-l'$, where \mathcal{C}_1
 17 is spanned by

$$\mathbf{g} + \gamma \mathbf{h}, \mathbf{g}^{[1]} + \gamma \mathbf{h}^{[1]}, \dots, \mathbf{g}^{[r]} + \gamma \mathbf{h}^{[r]}, \text{ where } r = n-k-1.$$

18 Similarly $\mathcal{C}_{pub}^{\perp [1]}$ contains a subcode of \mathcal{C}_2 of dimension $n-k-l'$, where \mathcal{C}_2 is
 19 spanned by

$$\mathbf{g}^{[1]} + \gamma^{[1]} \mathbf{h}^{[1]}, \mathbf{g}^{[2]} + \gamma^{[1]} \mathbf{h}^{[2]}, \dots, \mathbf{g}^{[r+1]} + \gamma^{[1]} \mathbf{h}^{[r+1]}.$$

20 Finally we have that $\mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}$ contains a subcode of $\mathcal{C} = \mathcal{C}_1 + \mathcal{C}_2$ of dimension
 21 at most $2(n-k-l')$, where \mathcal{C} is spanned by

$$\mathbf{g} + \gamma \mathbf{h} \text{ and } \mathbf{g}^{[1]}, \mathbf{h}^{[1]}, \dots, \mathbf{g}^{[r]}, \mathbf{h}^{[r]} \text{ and } \mathbf{g}^{[r+1]} + \gamma^{[1]} \mathbf{h}^{[r+1]}.$$

22 In the Coggia-Couvreur attack, the adversary can obtain (4) by computing
 23 (3). Our analysis shows that the adversary cannot perform the same operation on
 24 Modification II to obtain (4). Here we demonstrate this point with the method of
 25 reduction to absurdity.

Suppose that

$$\langle \mathbf{g}^{[r]} + \gamma^{[r]} \mathbf{h}^{[r]}, \mathbf{g}^{[r+1]} + \gamma^{[1]} \mathbf{h}^{[r+1]} \rangle \subseteq \bigcap_{i=0}^r (\mathcal{C}_{pub}^{\perp [i]} + \mathcal{C}_{pub}^{\perp [i+1]}). \quad (7)$$

26 Then for any $0 \leq i \leq r$, we have

$$\mathbf{g}^{[r]} + \gamma^{[r]} \mathbf{h}^{[r]}, \mathbf{g}^{[r+1]} + \gamma^{[1]} \mathbf{h}^{[r+1]} \in \mathcal{C}_{pub}^{\perp [i]} + \mathcal{C}_{pub}^{\perp [i+1]}. \quad (8)$$

27 Applying the inverse of the i -th Frobenius map to both sides of (8), there will be

$$\mathbf{g}^{[r-i]} + \gamma^{[r-i]} \mathbf{h}^{[r-i]}, \mathbf{g}^{[r-i+1]} + \gamma^{[1-i]} \mathbf{h}^{[r-i+1]} \in \mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]},$$

1 or equivalently

$$\mathbf{g} + \gamma\mathbf{h} \text{ and } \mathbf{g}^{[1]}, \mathbf{h}^{[1]}, \dots, \mathbf{g}^{[r]}, \mathbf{h}^{[r]} \text{ and } \mathbf{g}^{[r+1]} + \gamma^{[1]}\mathbf{h}^{[r+1]} \in \mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}.$$

2 This implies that $\mathcal{C} \subseteq \mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}$, which conflicts with the previous conclusion
 3 that $\mathcal{C}_{pub}^\perp + \mathcal{C}_{pub}^{\perp [1]}$ contains a subcode of \mathcal{C} of dimension at most $2(n - k - l)$.

4 Hence the assumption (7) cannot be true and the adversary cannot recover (4)
 5 from (3) as the Coggia-Couvreur attack on Loidreau's cryptosystem. Therefore
 6 the Coggia-Couvreur attack does not work on Modification II.

7 Parameters and key size

8 In Table 1 we give some parameters suggested for different security levels, and
 9 make a comparison on performance with Loidreau's original scheme in the case of
 10 $k \leq \frac{n}{2}$. When considering the parameters, we exploit the complexity assessment
 11 of generic attacks given in Section 6.

12 In Modification I, the public key is a systematic generator matrix of an $[n, k - l]$
 13 rank metric code, resulting in a public-key size of $(k - l)(n - k + l) \cdot m \cdot \log_2(q)$
 14 bits. In Modification II, the public key is a systematic generator matrix of an $[n, k]$
 15 rank metric code, resulting in a public-key size of $k(n - k) \cdot m \cdot \log_2(q)$ bits. As for
 16 information rates, this value is $(k - l)/n$ for Modification I, and k/n for Modification
 17 II respectively. For the concrete instances, we consider the case where $q = 3$ and
 18 $\lambda = 2$. It is not difficult to see from Table 1 that our modifications have obvious
 19 advantages over Loidreau's scheme in both public-key sizes and information rates.

Instance	Parameters	Public-key Size	Inf. Rate	Sec.
Loidreau's system	m=37, n=37, k=17	4,611	0.46	128
	m=45, n=45, k=21	8,425	0.47	192
	m=52, n=52, k=24	12,857	0.46	256
Modification I	m=42, n=42, k=23, l=2	3,670	0.50	128
	m=48, n=48, k=25, l=1	5,478	0.50	192
	m=56, n=56, k=29, l=1	8,698	0.50	256
Modification II	m=44, n=44, k=30, l=1	3,661	0.68	128
	m=51, n=51, k=33, l=1	6,002	0.65	192
	m=57, n=57, k=35, l=1	8,696	0.61	256

Table 1: Comparison on public-key sizes (in bytes) and information rates with Loidreau's scheme for different security levels.

20

21 In Table 2, we make a comparison on public-key sizes with some other code-
 22 based cryptosystems that were selected as the third round candidates of the NIST
 23 PQC Standardization Process. These candidates are HQC [37], BIKE [38], NTS-
 24 KEM [39] and Classic McEliece [40]. Note that the Classic McEliece published
 25 in the third round of the NIST PQC project is a merged version of NTS-KEM
 26 and the original Classic McEliece for their specifications being very similar. From

Instance	128 bits	192 bits	256 bits
HQC	2,249	4,522	7,245
BIKE	1,540	3,082	5,121
Classic McEliece	261,120	524,160	1,044,992
NTS-KEM	319,488	929,760	1,419,704
Modification I	3,693	5,478	8,698
Modification II	3,661	6,002	8,696

Table 2: Comparison on public-key sizes (in bytes) with some other cryptosystems.

1 Table 2 we can see that our modifications behave pretty well without using codes
2 endowed with special algebraic structures.

3 8 Conclusion

4 In this paper, we propose two modifications for Loidreau’s cryptosystem. Accord-
5 ing to our analysis, both of these two modifications can resist the existing structural
6 attacks on Gabidulin codes based cryptosystems, including Overbeck’s attack and
7 the Coggia-Couvreur attack. In our modifications, we adopt a systematic genera-
8 tor matrix of the public code to reduce the public-key size. Note that this method
9 of describing the public code may reveal some information about the plaintext be-
10 cause of the sparsity of the intended errors in Hamming metric [41], which means
11 a security flaw to the cryptosystem. In the rank metric, however, the intended
12 errors may happen in all coordinates of the error vector with high probability.
13 Particularly, if we generate the error vector by randomly and uniformly choosing
14 n elements from an \mathbb{F}_q -subspace of \mathbb{F}_q^m of dimension t , then the expected Ham-
15 ming weight of the subvector of length k is $k(1 - \frac{1}{q^t}) \sim k$, while in Hamming metric
16 this value is kt/n . Therefore there is no need to worry about this problem in our
17 modifications.

18 **Acknowledgements** This research is supported by the National Key Research and Develop-
19 ment Program of China (Grant No. 2018YFA0704703), the National Natural Science Founda-
20 tion of China (Grant No. 61971243), the Natural Science Foundation of Tianjin (20JCZDJC00610),
21 and the Fundamental Research Funds for the Central Universities of China (Nankai Univer-
22 sity).

23 References

- 24 1. McEliece, R.J.: A public-key cryptosystem based on algebraic coding theory. *Jet Propuls.*
25 *Lab. DSN Progr. Rep.* 42-44, 114–116 (1978).
- 26 2. Canteaut, A., Sendrier, N.: Cryptanalysis of the original McEliece cryptosystem. In: Ohta,
27 K., Pei, D. (Eds.): *Proceedings of ASIACRYPT’98*, LNCS, vol. 1514, pp. 187–199. Springer
28 (2000).
- 29 3. Lee, P.J., Brickell, E.F.: An observation on the security of McEliece’s public-key cryptosys-
30 tem. In: Guenther, C.G. (Ed.): *Proceedings of Advances in Cryptology–EUROCRYPT’88*,
31 LNCS, vol. 330, pp. 275–280. Springer (1988).
- 32 4. Kobara, K., Imai, H.: Semantically secure McEliece public-key cryptosystems-conversions
33 for McEliece PKC. Kim, K. (Ed.): *Proceedings of PKC 2001*, LNCS, vol. 1992, pp. 19–35.
34 Springer (2001).

- 1 5. Faugère, J.-C., Otmani, A., Perret, L., Portzamparc, F.de., Tillich, J.-P.: Structural crypt-
2 analysis of McEliece schemes with compact keys. *Des. Codes Cryptogr.* 79(1), 87–112
3 (2016).
- 4 6. Loidreau, P., Sendrier, N.: Weak keys in the McEliece public-key cryptosystem. *IEEE*
5 *Trans. Inf. Theory* 47(3), 1207–1211 (2001).
- 6 7. Niederreiter, H.: Knapsack-type cryptosystems and algebraic coding theory. *Prob. Control*
7 *and Inf. Theory* 15(2), 159–166 (1986).
- 8 8. Sidelnikov, V.M., Shestakov, S.O.: On insecurity of cryptosystems based on generalized
9 Reed-Solomon codes. *Discret. Math. Appl.* 2(4), 439–444 (1992).
- 10 9. Li, Y.X., Deng, R.H., Wang, X.M.: On the equivalence of McEliece's and Niederreiter's
11 public-key cryptosystems. *IEEE Trans. Inf. Theory* 40(1), 271–273 (1994).
- 12 10. Baldi, M., Bianchi, M., Chiaraluce, F., Rosenthal, J., Schipani D.: Enhanced public key
13 security for the McEliece cryptosystem. *J. Cryptology* 29(1), 1–27 (2016).
- 14 11. Couvreur, A., Gaborit, P., Otmani, A., Tillich, J.-P.: Distinguisher-based attacks on
15 public-key cryptosystems using Reed-Solomon codes. *Des. Codes Cryptogr.* 73(2), 641–
16 666 (2014).
- 17 12. Gabidulin, E.M.: Theory of codes with maximum rank distance. *Prob. Peredachi Inf.* 21(1),
18 3–16 (1985).
- 19 13. Loidreau, P.: A Welch-Berlekamp like algorithm for decoding Gabidulin codes. In: Ytrehus,
20 \emptyset . (Ed.): *Proceedings of WCC 2005, LNCS*, vol. 3969, pp. 36–45. Springer (2005).
- 21 14. Richter, G., Plass, S.: Error and erasure decoding of rank-codes with a modified Berlekamp-
22 Massey algorithm. *ITG FACHBERICHT*, pp. 203–210 (2004).
- 23 15. Chabaud, F., Stern, J.: The cryptographic security of the syndrome decoding problem
24 for rank distance codes. In: *Proceedings of International Conference on the Theory and*
25 *Application of Cryptology and Information Security*, pp. 368–381. Springer (1996).
- 26 16. Ourivski, A.V., Johansson, T.: New technique for decoding codes in the rank metric and
27 its cryptography applications. *Probl. Inf. Transm.* 38(3), 237–246 (2002).
- 28 17. Gabidulin, E.M., Paramonov, A.V., Tretjakov, O.V.: Ideals over a non-commutative ring
29 and their application in cryptology. In: Davies, D.W. (Ed.): *Proceedings of Advances in*
30 *Cryptology-EUROCRYPT'91, LNCS*, vol. 547, pp. 482–489. Springer (1991).
- 31 18. Rashwan, H., Gabidulin, E.M., Honary, B.: Security of the GPT cryptosystem and its
32 applications to cryptography. *Secur. Commun. Netw.* 4(8), 937–946 (2011).
- 33 19. Gabidulin, E.M.: Attacks and counter-attacks on the GPT public key cryptosystem. *Des.*
34 *Codes Cryptogr.* 48(2), 171–177 (2008).
- 35 20. Gabidulin, E.M., Rashwan, H., Honary, B.: On improving security of GPT cryptosystems.
36 In: *Proceedings of 2009 IEEE International Symposium on Information Theory*, pp. 1110–
37 1114. IEEE (2009).
- 38 21. Loidreau, P.: Designing a rank metric based McEliece cryptosystem. In: Sendrier, N. (Ed.):
39 *Proceedings of PQCrypto 2010, LNCS*, vol. 6061, pp. 142–152. Springer (2010).
- 40 22. Rashwan, H., Gabidulin, E.M., Honary, B.: A smart approach for GPT cryptosystem based
41 on rank codes. In: *Proceedings of 2010 IEEE International Symposium on Information*
42 *Theory*, pp. 2463–2467. IEEE (2010).
- 43 23. Gibson, K.: The security of the Gabidulin public key cryptosystem. In: *Proceedings of*
44 *Advances in Cryptology-EUROCRYPT'96, LNCS*, vol. 1070, pp. 212–223. Springer (1996).
- 45 24. Overbeck, R.: Structural attacks for public key cryptosystems based on Gabidulin codes.
46 *J. Cryptology* 21(2), 280–301 (2008).
- 47 25. Horlemann-Trautmann, A.-L., Marshall, K., Rosenthal, J.: Extension of Overbeck's attack
48 for Gabidulin-based cryptosystems. *Des. Codes Cryptogr.* 86(2), 319–340 (2018).
- 49 26. Faure, C., Loidreau, P.: A new public-key cryptosystem based on the problem of recon-
50 structing p -polynomials. In: Ytrehus, \emptyset . (Ed.): *Proceedings of WCC 2005, LNCS*, vol.
51 3969, pp. 304–315. Springer (2005).
- 52 27. Gaborit, P., Otmani, A., Kalachi, H.T.: Polynomial-time key recovery attack on the Faure-
53 Loidreau scheme based on Gabidulin codes. *Des. Codes Cryptogr.* 86(7), 1391–1403 (2018).
- 54 28. Otmani, A., Kalachi, H.T., Ndjeya, S.: Improved cryptanalysis of rank metric schemes
55 based on Gabidulin codes. *Des. Codes Cryptogr.* 86(9), 1983–1996 (2018).
- 56 29. Loidreau, P.: A new rank metric codes based encryption scheme. In: Lange, T., Takagi, T.
57 (Eds.): *Proceedings of PQCrypto 2017, LNCS*, vol. 10346, pp. 3–17. Springer (2017).
- 58 30. Coggia, D., Couvreur, A.: On the security of a Loidreau rank metric code based encryption
59 scheme. *Des. Codes Cryptogr.* 88(9), 1941–1957 (2020).
- 60 31. Ghatak, A.: Extending Coggia-Couvreur attack on Loidreau's rank-metric cryptosystem.
61 [arXiv:2007.07354 \[cs.IT\]](https://arxiv.org/abs/2007.07354) (2020).

- 1 32. Ling, S., Xing, C.: Coding theory: A First Course. Cambridge University Press (2004).
- 2 33. Gabidulin, E.M., Ourivski, A.V., Honary, B., Ammar, B.: Reducible rank codes and their
3 applications to cryptography. *IEEE Trans. Inf. Theory* 49(12), 3289–3293 (2003).
- 4 34. Horlemann-Trautmann, A.-L., Marshall, K.: New criteria for MRD and Gabidulin codes
5 and some rank-metric code constructions. arXiv:1507.08641 [cs.IT] (2015).
- 6 35. Horlemann-Trautmann, A.-L., Marshall, K., Rosenthal, J.: Considerations for rank-based
7 cryptosystems. In: *Proceedings of 2016 IEEE International Symposium on Information*
8 *Theory*, pp. 2544–2548. IEEE (2016).
- 9 36. Gaborit, P., Ruatta, O., Schrek, J.: On the complexity of the rank syndrome decoding
10 problem. *IEEE Trans. Inf. Theory* 62(2), 1006–1019 (2016).
- 11 37. Melchor, C.A., Aragon, N., et al.: Hamming quasi-cyclic (HQC). [http://pqc-hqc.org/
12 doc/hqc-specification_2020-10-01.pdf](http://pqc-hqc.org/doc/hqc-specification_2020-10-01.pdf). Accessed October 10, 2020.
- 13 38. Aragon, N., Barreto, P.S., et al.: BIKE: bit flipping key encapsulation. [https://
14 bikesuite.org/files/v4.1/BIKE_Spec.2020.10.22.1.pdf](https://bikesuite.org/files/v4.1/BIKE_Spec.2020.10.22.1.pdf). Accessed October 10, 2020.
- 15 39. Albrecht, M., Cid, C., Paterson, K.G., et al.: NTS-KEM. [https://drive.google.com/
16 file/d/1N3rv4HKCt9yU4xn6wuepsBUrfQW8cuFy/view](https://drive.google.com/file/d/1N3rv4HKCt9yU4xn6wuepsBUrfQW8cuFy/view). Accessed November 29, 2019.
- 17 40. Albrecht, M.R., Bernstein, D.J., et al.: Classic McEliece: conservative code-based cryptog-
18 raphy. <https://classic.mceliece.org/nist/mceliece-20201010.pdf>. Accessed October
19 10, 2020.
- 20 41. Canteaut, A., Chabaud, F.: Improvements of the attacks on cryptosystems based on
21 error-correcting codes. Rapport interne du Departement Mathematiques et Informatique,
22 LIENS-95-21 (1995).