

# Overflow-detectable Floating-point Fully Homomorphic Encryption

Seunghwan Lee and Dong-Joon Shin

Department of Electronic Engineering, Hanyang University,  
Seoul , South Korea  
{kr3951, djshin}@hanyang.ac.kr

**Abstract.** We propose a floating-point fully homomorphic encryption (FPFHE) is proposed based on torus fully homomorphic encryption equipped with programmable bootstrapping [15]. Specifically, FPFHE for 32-bit and 64-bit floating-point messages is implemented, which is state-of-the-art in terms of precision. Also, a ciphertext is constructed to check if an overflow had occurred or not while evaluating arithmetic circuits with FPFHE, which is useful when the message space or arithmetic circuit is too complex to estimate a bound of outputs such as deep learning applications.

**Keywords:** Fully homomorphic encryption, homomorphic floating-point arithmetic, overflow detection, subgaussian error analysis

## 1 Introduction

Since Gentry’s seminal work on fully homomorphic encryption (FHE) [17], various FHEs such as BGV/FV [7], FHEW/TFHE [23, 13], and CKKS [11] have been proposed and intensively studied. Note that they use integers, bits, or approximated complex numbers as their message sets. FHE is a powerful methodology for evaluating any function while keeping the privacy of data. As applications of FHE with boolean circuit, deniable FHE [1], private information retrieval (PIR) [18, 21], private set intersection (PSI) [4], and homomorphic transpiler[?] have been studied. Also, homomorphically evaluating machine and deep learning models such as image classification [6] have been mostly studied by using CKKS. Since CKKS deals with a ciphertext packed with multiple messages, circuits which can evaluate parallel with a large data are very suitable for CKKS. Moreover, no other FHE can process real messages with high precision except CKKS <sup>1</sup>. Therefore, CKKS is widely used to evaluating deep neural networks (DNNs).

However, in CKKS, errors from encoding floating-point numbers to the message space cannot be avoided. Since many DNNs are learned with floating-point data and arithmetic, CKKS operations inevitably introduce loss of accuracy. Without solving such encoding error problem, CKKS may not guarantee sat-

---

<sup>1</sup> [14] implements DNNs with 5-bit precision by using TFHE.

isfactory results for the applications requiring complex and accurate results such as privacy-preserving generative models [5]. Therefore, floating-point FHE (FPFHE) is required for achieving equivalent accuracy of results on plaintexts.

Another problem is an overflow such that evaluating deep arithmetic circuit returns irrelevant result when the circuit output takes a value out of the message space. However, in contrast to evaluation using plaintexts, overflow is very hard to detect in ciphertext domain. Such overflow frequently occurs if a value of circuit output is not bounded or the input dimension of circuit is too large, then every input cannot be ensured whether it generates an overflow occurs or not. Also, when circuit parameters have been updated by the past data as in privacy preserving federated learning [21], then inaccurate updating using overflow ruins the circuit performance. However, to our best of knowledge, an overflow detection for FHE has not been proposed.

**Contributions** First, we propose a floating-point FHE (FPFHE), which effectively resolves the error problem from encoding floating-point numbers and makes every operation on ciphertexts synchronized to the corresponding operation on plaintexts from floating-point message space. Moreover, we implement FPFHE with single (32-bit) and double (64-bit) precision, which show much better precision than the state-of-the art CKKS with 40-bit fixed-point precision [22]. Second, an effective overflow-detection (OD) method for the proposed FPFHE is constructed, which can check whether an overflow occurs or not during the homomorphic operations. By combining these two schemes, we construct OD-FPFHE. Also, we propose algorithms handling the following technical issues, which are important components of OD-FPFHE.

- **Sequential bootstrapping** In FHE, bootstrapping algorithm is required for reducing the error after homomorphic operations. We extend the method in [15] to bootstrap a larger number of messages bit by using integers modulo number theoretic transform(NTT)-friendly  $Q$ . This algorithm enables to bootstrap more message bits and to use NTT algorithm which is one of the solutions for removing errors generated from fast Fourier transform (FFT), denoted as an open problem in [15].
- **Accelerating deterministic gadget decomposition using modulus  $Q$**  This algorithm is performed by using 64-bit integer operations when an integer modulus  $Q = Q_0Q_1 > 2^{64}$  is chosen such that  $Q_0$  and  $Q_1$  are NTT-friendly primes.
- **Modified blind rotation for GINX-bootstrapping** This algorithm keeps the number of NTT operations constant for any secret key having finite support and hence improves running time compared to the existing algorithm [23] when ternary or larger secret key is used.
- **Error analysis without independent heuristic** This improved analysis can be applicable even when deterministic gadget decomposition is used and enable choosing a small lattice parameters for enhancing operation times.
- **Various homomorphic algorithms** Algorithms such as evaluating min and max, lifting a constant message to a monomial exponent, counting consecu-

tive zeros from the most significant in the fraction of floating-point message until non-zero value occurs, and performing carry over after operation of two floating-point numbers are proposed. Note that these algorithms are run by using sequential bootstrapping without secret key.

**Related works** Several methods to implement FPFHE have been suggested [20, 24]. However, these FPFHE do not normalize results after homomorphic operations (See Section 2.6), and suffer from slow operation time. For error analysis without independent heuristic, Case, *et al.*[10] proves that average-case error analysis of [13] does not require independent heuristic when randomized gadget decomposition is used.

## 2 Preliminaries

In this section, mathematical backgrounds and several fully homomorphic encryption schemes are introduced. The main reference and notation of algebraic and statistical background are followed [9], [27], and [30].

### 2.1 Notation

Let  $\mathbb{N}, \mathbb{Z}, \mathbb{Q}$ , and  $\mathbb{C}$  be a set of natural numbers, integer numbers, rational numbers, and complex numbers, respectively. Let  $\mathbb{Z}_q \cong \mathbb{Z}/q\mathbb{Z}$  be an integer ring  $\mathbb{Z}$  modulo  $q\mathbb{Z}$  for some  $q \in \mathbb{N}$ , and let  $\mathbb{Z}_q[X]$  be a polynomial ring  $\mathbb{Z}[X]$  modulo  $q\mathbb{Z}[X]$ . We will use  $[n]$  to denote an index set  $0, 1, \dots, n-1$  for  $n \in \mathbb{N}$ . More generally,  $[n_1, n_2, \dots, n_m] = \prod_{i=1}^m [n_i]$  is used as a product index set for  $n_1, \dots, n_m \in \mathbb{N}$ .

We will use notation  $\mathbf{a} = (a_i)_{i \in [n]}$  as a vector notation and  $a_i$  as a  $i$ -th element of  $\mathbf{a}$ . Analogously for any polynomial  $a(X) \in \mathbb{Z}[X]$ , we will use  $a_i$  to denote the coefficient of  $X^i$  in  $a(X)$ . When a vector  $\mathbf{a}(X) \in \mathbb{Z}^n[X]$  are given,  $a_i(X)$  denotes the  $i$ -th element of  $\mathbf{a}(X)$  and  $a_{i,j}$  is the  $j$ -th coefficient of the  $a_i(X)$ .

To measure the magnitude of element, we always use  $l_1$  metric  $|\cdot|$  for  $x \in \mathbb{R}$ . For any vector  $\mathbf{x} \in \mathbb{R}^n$ ,  $|\mathbf{x}|$  be a maximum value of  $|x_i|$  and for all  $i \in [n]$ . If  $x \in \mathbb{Z}_q$ ,  $|x|$  is defined by choosing the representation  $\bar{x}$  over  $-q/2 \leq \bar{x} < q/2$  and evaluating  $|\bar{x}|$ . Analogously, if  $x \in \mathbb{Z}_q[X]$  than  $|x|$  is defined as maximum among  $|x_i|$ .

We represent a natural number  $x \in \mathbb{N}$  by  $x = (x_n x_{n-1} \dots x_1 x_0)_{(\beta)}$  for a given  $\beta \geq 2$  if

$$x = x_0 + x_1\beta + \dots + x_n\beta^n,$$

where  $0 \leq x_0, \dots, x_n < \beta$  and  $\beta$  is called a radix.

### 2.2 Algebraic background

Let  $\Phi_{2N}(X) \in \mathbb{Q}[X]$  be a cyclotomic polynomial with order  $2N \in \mathbb{N}$ . If  $N$  is a power of two, then  $\Phi_{2N}(X)$  is known to be  $X^N + 1 \in \mathbb{Q}[X]$  which is used in

this paper. Let  $R_N \triangleq \mathbb{Z}[X]/(X^N + 1)$  be the quotient polynomial ring with ideal  $(X^N + 1)$ , and let  $R_{N,q} \triangleq \mathbb{Z}[X]/(X^N + 1, q) \cong \mathbb{Z}_q[X]/(X^N + 1)$  be the quotient polynomial ring with ideal  $(X^N + 1, q)$  for a positive integer  $q \in \mathbb{Z}$ . It is clear that product of  $a(X), b(X) \in R_{N,q}$  is

$$a(X)b(X) = \sum_{j \in [N]} \left[ \sum_{i \in [j]} a_i b_{j-i} - \sum_{i=j+1}^{N-1} a_i b_{N+j-i} \right] X^j,$$

having the property that  $a_i$  and  $b_i$  for all  $i \in [N]$  participate only once for all in each coefficient of  $a(X)b(X)$ . This property is called as *negacyclic property*.

If  $Q$  is a prime number satisfying  $2N|(Q-1)$ , then a field  $\mathbb{Z}_Q$  splits  $\Phi_{2N}(X)$  and has a primitive  $2N$ -th root of unity  $\zeta \in \mathbb{Z}_Q$  such that, by the Chinese remainder theorem(CRT), there is an isomorphism as follows:

$$\psi : R_{N,Q} \rightarrow \mathbb{Z}_Q^N, \quad a(X) \mapsto (a(\zeta), a(\zeta^3), \dots, a(\zeta^{2N-1}))$$

We will call  $Q$  as NTT-friendly  $Q$  if  $Q$  satisfies  $2N|(Q-1)$ .

More generally, if  $Q = Q_0 Q_1 \dots Q_{n-1} \in \mathbb{N}$  with NTT-friendly primes  $Q_i$  for all  $i \in [n]$ , there exist isomorphisms being the inverse functions of each other as follows:

$$\begin{aligned} \phi : \mathbb{Z}_Q &\rightarrow \prod_{i \in [n]} \mathbb{Z}_{Q_i}, & a &\mapsto (a \bmod Q_0, \dots, a \bmod Q_{n-1}) \\ \phi^{-1} : \prod_{i \in [n]} \mathbb{Z}_{Q_i} &\rightarrow \mathbb{Z}_Q, & (a_0, \dots, a_{n-1}) &\mapsto \left( \sum_{i \in [n]} a_i Q_i^* \hat{Q}_i \right) \bmod Q \end{aligned} \quad (1)$$

where  $Q_i^* = Q/Q_i$ , and  $\hat{Q}_i = Q_i^{*-1} \bmod Q_i$ . Let NTT-friendly primes  $(Q_0 = \nu 2^{n_0} + 1, Q_1 = \nu 2^{n_1} + 1)$  be denoted as *shared primes* when these share a same scaling factor  $\nu \in \mathbb{N}$ . In this paper, *shared primes* are used as a integer modulus after Section 3.1.

### 2.3 Statistical background

Let  $(\Omega, \mathcal{F}, \mathbb{P})$  be an ambient probability space and  $X : \Omega \rightarrow \mathbb{R}$  be an one-dimensional random variable. When the co-domain of random variable is defined in a finite ring  $\mathbb{Z}_Q$ , we always define  $X$  as a function using  $\Omega \rightarrow \{-\lfloor Q/2 \rfloor, \dots, \lfloor Q/2 \rfloor - 1\}$ . We call random variable  $X$  is  $B$ -bounded if  $|X| \leq B$  almost surely. We will briefly explain subgaussian random variable and its properties.

**Definition 1 ([9]).** A random variable  $X$  is a subgaussian random variable with a standard parameter  $\sigma \geq 0$ , denoted as  $X \sim \text{subG}(\sigma)$ , if  $\mathbb{E}[X] = 0$  and the moment generating function  $M_X(v)$  is bounded as follows:

$$M_X(t) \triangleq \mathbb{E}[\exp(tX)] \leq \exp(\sigma^2 t^2 / 2).$$

**Proposition 1 ([9]).** For any random variable  $X \sim \text{subG}(\sigma)$ ,  $X$  is  $O(\sigma\sqrt{v})$ -bounded except with  $2^{-\Omega(v)}$  probability.

It is also known that the space of subgaussians forms an  $\mathbb{R}$ -vector space from following properties. (i) If  $X \sim \text{subG}(\sigma_X)$  and  $Y \sim \text{subG}(\sigma_Y)$ , then  $X + Y \sim \text{subG}(\sigma_X + \sigma_Y)$ . (ii) For any scaling  $c \in \mathbb{R}$ ,  $cX \sim \text{subG}(|c|\sigma_X)$ . (iii) Moreover, if  $X$  and  $Y$  are independent,  $X + Y \sim \text{subG}((\sigma_X^2 + \sigma_Y^2)^{1/2})$ .

Since (iii) is the best analytical result for sum of two random variables in terms of minimizing variance, we will focus on condition when (iii) holds without independence. Random variables  $X_i \sim \text{subG}(\sigma_i)$  for  $i \in [n]$  are called to have *Pythagorean additivity* if  $\sum_{i \in [n]} X_i \sim \text{subG}((\sum_{i \in [n]} \sigma_i^2)^{1/2})$  and the following conditions have been investigated.

**Lemma 1 (Sum of two dependent subgaussians [10]).** *If  $Z_0$  is  $\text{subG}(\sigma_0)$  and for  $1 \leq i \leq n-1$ ,  $(Z_i | Z_0, \dots, Z_{i-1})$  is  $\text{subG}(\sigma_i)$  and  $\sigma_i$  is free of  $Z_0, \dots, Z_{i-1}$  and  $\mathbb{E}[Z_i] = 0$ , then  $Z_0, \dots, Z_{n-1}$  have Pythagorean additivity.*

**Corollary 1 (From Lemma 1 [10]).** *Let  $Y_i$  are mutually independent  $B_Y$ -bounded subgaussian random variables for all  $i \in [n]$ , and let  $X_i$  are  $B_X$ -bounded subgaussian random variables for all  $i \in [n]$  where  $X_i$  depends only on  $X_j$  and  $Y_j$  for all  $j < i$ . Then  $X_0 Y_0, \dots, X_{n-1} Y_{n-1}$  have Pythagorean additivity.*

Corollary 1 ensures that although all  $X_i Y_i$  is dependent to each others, analytical result of variance is the same as when  $X_i Y_i$  are assumed to be mutually independent. This property is useful for analyzing a sum of large numbers of dependent random variables, e.g. analysing an error bound after bootstrapping is performed in FHE. However, Corollary 1 requires zero mean bounded random variables  $X_i$ , and  $Y_i$  since  $X_i$  and  $Y_i$  are subgaussian random variables. The same analytic result under more relaxed condition is derived in Section 4.1.

## 2.4 LWE/MLWE symmetric encryption and gadget decomposition

In this section, widely used lattice-based encryption schemes are introduced. First, we recall the LWE symmetric encryption [29]. For any given natural number  $q, n, t \in \mathbb{N}$ , and  $t$ -bit message space  $\mathbb{Z}_{2^t}$ , a ciphertext of  $m \in \mathbb{Z}_{2^t}$  with symmetric key  $\mathbf{s} = (-s_1, \dots, -s_n, 1) \in \mathbb{Z}_q^{n+1}$  is obtained as

$$\text{ct}[m] \triangleq (\mathbf{a}, b = \sum_{i=1}^n a_i s_i + m \lfloor q/2^t \rfloor + e)^T \in \mathbb{Z}_q^{(n+1) \times 1},$$

where  $T$  refers to the transposition of matrix,  $\mathbf{a} \in \mathbb{Z}_q^n$  is chosen from a uniform distribution and  $e$  is sampled from a centered discrete gaussian distribution  $\chi_e$  on  $\mathbb{Z}$  with standard deviation  $\sigma$ , and a secret key  $\mathbf{s}$  sampled from a distribution  $\chi_s$ . We adopt a ternary secret key  $\mathbf{s}$  which is widely used for homomorphic encryption [2]. In addition, secret key  $\mathbf{s}$  for LWE encryption is called  $h$ -sparse if the number of non zero element  $\mathbf{s}$  is  $h$ .

The decryption function  $\varphi_{\mathbf{s}}$  of LWE encryption is defined as a  $\mathbb{Z}_q$ -linear functional as follows:

$$\varphi_{\mathbf{s}}(\text{ct}[m \lfloor q/2^t \rfloor]) \triangleq b - \sum_{i=1}^n a_i s_i = m \lfloor q/2^t \rfloor + e \in \mathbb{Z}_q.$$

Therefore, if  $\lceil \log e \rceil \leq \lfloor \log q \rfloor - t$  is satisfied, then the message  $m$  is correctly extracted from  $\text{ct}[m]$  and in that case, we call  $\mathbf{ct}$  as a *valid* ciphertext.

Based on  $R_{N,Q}$ , we can define module-LWE (MLWE) ciphertext as follows:

$$\text{CT}[m(X)[Q/2^t]] \triangleq (a(X), b(X)) = \sum_{i \in [K]} a_i(X)s_i(X) + m(X)[Q/2^t] + e(X))^T,$$

where  $\text{CT} \in R_{N,Q}^{(K+1) \times 1}$  and every coefficient of  $s_i(X)$  and  $e(X)$  is sampled from  $\chi_e$  and  $\chi_s$ , respectively. Security reduction of LWE and MLWE from shortest independent vector problem (SIVP) on general lattice or structured Minkowski space (number field) [27], and general reductions between MLWEs have been researched [25].

Especially, following the tight reduction from MLWE to LWE are widely used in FHEs [13, 23]:

$$\begin{aligned} \mathbf{ct}[m_\alpha] &\leftarrow \mathbf{SampleExtract}(\text{CT}[m(X)] \triangleq (a_1(X), \dots, a_K(X), b(X)), \alpha) \\ &\triangleq (a'_{(0,0)}, \dots, a'_{(1,N-1)}, a'_{(2,1)}, \dots, a'_{(K-1,N-1)}, b_\alpha) \in \mathbb{Z}_Q^{KN+1}, \end{aligned} \quad (2)$$

where  $a'_{(i,n)} = a_{i,(\alpha-n)}$  for  $0 \leq n \leq \alpha$ ,  $a'_{(i,n)} = -a_{(i,N-n)}$  for  $\alpha < n \leq N$ , for all  $i \in [K]$ . Then,  $\mathbf{ct}[m_\alpha]$  is a *valid* LWE ciphertext for the secret key  $\mathbf{s} = (s_{(0,0)}, \dots, s_{(0,N-1)}, s_{(1,0)}, \dots, s_{(K-1,N-1)})$  from the secret key  $\mathbf{s}(X)$  of  $\text{CT}[m(X)]$ .

In this paper, LWE and MLWE ciphertexts are denoted as  $\mathbf{ct}$  and  $\text{CT}$  when the message is clear in context. In addition, for a given  $N$ , a ciphertext  $\mathbf{ct}$  is called a *squashed* if integer modulus of  $\mathbf{ct}$  is  $2N$ . Note that *squashed*  $\mathbf{ct}$  is used to introduced FHEW / TFHE schemes in Section 2.5.

Next, we will review an approximated gadget for decomposing on MLWE ciphertext.

**Definition 2 ([16]).** For any finite additive group  $\mathfrak{R}$ ,  $\mathfrak{R}$ -gadget of size  $l$  with a quality  $\rho$  and a precision  $\epsilon$  is a vector  $\mathbf{g} \in \mathfrak{R}^l$  such that any element  $u \in \mathfrak{R}$  can be written as an approximated integer combination  $\sum_i g_i \cdot x_i$  which satisfies  $u - \sum_i g_i \cdot x_i = A$  for some gadget error  $A \in \mathfrak{R}$  with  $|A| \leq \epsilon$ , where  $\mathbf{x} = (x_1, \dots, x_w)$  has a norm at most  $\max_i |x_i| \leq \rho$ .

**Proposition 2 (Deterministic (signed) gadget decomposition [13, 23]).** Assume that two finite additive group  $R_{N,Q}$  and  $\mathbb{Z}_Q$ ,  $B \in \mathbb{N}$ , and  $\bar{l} \in \mathbb{N}$  are given such that  $B^{\bar{l}-1} \leq Q < B^{\bar{l}}$ . Then, there exists a gadget  $\mathbf{g} = (B^{\bar{l}-1}, \dots, B^{\bar{l}-1})$  and deterministic gadget decompositions  $G_1^{-1} : R_{N,Q} \rightarrow R_{N,Q}^{1 \times \bar{l}}$  and  $G_2^{-1} : \mathbb{Z}_Q \rightarrow \mathbb{Z}_Q^{1 \times \bar{l}}$  with a quality  $\rho = \lceil B/2 \rceil$  and a precision  $\epsilon = \lceil B^{\bar{l}-1}/2 \rceil$ .

By using gadget decomposition, Gentry, Sahai, and Waters (GSW) [19] ciphertext and operation between GSW and MLWE ciphertexts are introduced in next section.

## 2.5 Some fully homomorphic encryption for constructing OD-FPFHE: GSW, FHEW and TFHE

GSW cryptosystem will be reviewed, which is necessary for constructing bootstrapping algorithms. Let  $I_n \in R_{N,Q}^{n \times n}$  be the identity matrix and  $\otimes$  be the kronecker product. Then for given message  $m \in \{0, 1\}$ , MLWE secret key  $\mathbf{s}(X)$  and  $R_{N,Q}$ -gadget  $\mathbf{g}$  from Proposition 2, GSW ciphertext  $\text{GCT} \in R_{N,Q}^{l(K+1) \times (K+1)}$  is defined as a matrix as follows:

$$\text{GCT}[m] \triangleq \left( \text{CT} \left[ mS_0(X) \right] \middle| \text{CT} \left[ mS_1(X) \right] \middle| \dots \middle| \text{CT} \left[ mS_{l(K+1)-1}(X) \right] \right)^T,$$

where  $\mathbf{S}(X) = (I_{K+1} \otimes \mathbf{g})\mathbf{s}(X)$ .

Moreover given two ciphertexts  $\text{CT}[m_1(X)]$  and  $\text{GCT}[m_2]$ , external product  $\boxtimes$  is defined as follows:

$$\boxtimes : \text{CT} \times \text{GCT} \rightarrow \text{CT}, \quad (\text{CT}, \text{GCT}) \mapsto \text{G}^{-1}(\text{CT})\text{GCT}.$$

Decryption result of  $\text{GCT} \boxtimes \text{CT}$  is already known as follows [13]:

$$\begin{aligned} & \varphi_{\mathbf{s}(X)}(\text{CT} \boxtimes \text{GCT}) \\ &= m_2 m_1(X) + m_2 e'(X) + \sum_{i \in [l(K+1)]} e_i(X) \text{G}^{-1}(\text{CT})_i + \sum_{i \in [K+1]} s_i(X) A'_i(X) \end{aligned} \quad (3)$$

where  $\mathbf{e}(X) \in R_{N,Q}^{l(K+1)}$  is a noise contained in  $\text{GCT}$ ,  $e'(X)$  is a noise contained in  $\text{CT}$ , and a  $A'_i(X)$  is a gadget error. Since every norm value of  $e_i(X)$  and  $s_i(X)$  are small, validity of  $\text{GCT} \boxtimes \text{CT}$  depends on  $\rho$  and  $\epsilon$  of gadget decomposition.

Given LWE ciphertext  $\mathbf{ct}$ , bootstrapping algorithm of FHEW and TFHE executes the following contents. (i) the modulus of  $\mathbf{ct}$  is reduced to a *valid squashed*  $\mathbf{ct}'[m] = (a_1, \dots, a_n, b)$  with  $m = (m_{t-1}, \dots, m_0)_{(2)} 2^v$  for  $v = \log 2N - t$  and add the bias to  $b$  of  $\mathbf{ct}'$  [23]. (ii) **BlindRotate** (See Algorithm 2 in Section 4.2) with public polynomial  $\text{ACCPoly}(X) \in R_{N,Q}$  is run and following MLWE ciphertext <sup>2</sup>:

$$\text{CT} \left[ (-1)^{m_{t-1}} \text{ACCPoly}(X) X^{-\varphi_{\mathbf{s}}(\mathbf{ct})} \right] \quad (4)$$

is obtained. (iii) *valid*, LWE ciphertext  $\mathbf{ct}''$  with constant message of (4) is extracted by using **SampleExtract** defined in (2). (iv) secret-key of  $\mathbf{ct}''$  is switched to secret-key of  $\mathbf{ct}$ .

The correctness of bootstrapping algorithm depends of validity of *squashed*  $\mathbf{ct}'$  and having zero of most significant bit (MSB), i.e.  $m_{t-1} = 0$ . Recently, programmable bootstrapping (PBS) is proposed, which enables that server can evaluates a look-up table on ciphertext by programming the coefficients of  $\text{ACCPoly}(X)$  [15]. In addition, a without padding PBS (WoP-PBS) algorithm is proposed that above bootstrapping process still correct when  $m_{t-1} = 1$ . In this paper, WoP-PBS is applied to a  $R_{N,Q}$ , where  $Q$  consisted of *shared primes* in Section 4.3.

<sup>2</sup> In this paper  $-\varphi_{\mathbf{s}}(\mathbf{ct})$  is located on monomial degree in (4), instead of  $\varphi_{\mathbf{s}}(\mathbf{ct})$  [13].

## 2.6 Introduction to floating-point number systems

A floating-point number system can be defined by using four parameters as follows:

**Definition 3 ([26]).** A  $(\beta, p, e_{\min}, e_{\max})$  floating-point number system is defined by four integers: (i) a radix  $\beta \geq 2$ , (ii) a precision  $p \geq 2$ , (iii) two extreme exponents  $e_{\min}$  and  $e_{\max}$  with  $e_{\min} < e_{\max}$ , such that every floating-point number  $x \in \mathbb{R}$  has at least one representation  $(s, m, e)$  satisfying

$$x = s \cdot m \cdot \beta^e, \quad (5)$$

where  $s \in \{1, -1\}$  is the sign bit of  $x$ ,  $m$  is an integer satisfying  $0 \leq m < \beta$ , and  $e$  is an integer satisfying  $e_{\min} \leq e \leq e_{\max}$ .

We call  $m$  and  $s$  as fraction and exponent in (5), respectively. Since Definition 3 does not guarantee uniqueness of floating-point representation  $(s, m, e)$ , a unique representation, called *normal form*<sup>3</sup> as follows:

**Definition 4 ([26]).** For the  $(\beta, p, e_{\min}, e_{\max})$ -floating-point number system,  $(s, m, e)$  of  $x \in \mathbb{R}$  is a normal form if  $1 \leq m < \beta$  or if  $e = e_{\min}$  with  $0 \leq m < 1$ .

Intuitively, a fraction  $m$  can be expressed as  $(m_{p-1}.m_{p-2}\dots m_1 m_0)_{(\beta)}$ . If  $x > \beta^{e_{\min}}$ , then we can choose the unique fraction with  $m_{p-1} > 0$ . Otherwise, we uniquely choose the  $m$  with  $e = e_{\min}$ .

Let  $\text{RZ} : \mathbb{R} \rightarrow \mathbb{R}$  be a rounding function to a floating-point number such that  $\text{RZ}(x)$  rounds down if  $x \geq 0$ , rounds up otherwise [26]. Then following proposition are known.

**Proposition 3 (Chapter 5 of [26]).** Let  $\top \in \{+, -, \cdot, \setminus\}$  be the arithmetic operation. If  $x, y \in \mathbb{R}$  with  $\beta^{e_{\min}} \leq |x \top y| \leq (\beta - \beta^{1-p})\beta^{e_{\max}}$  are given, following inequality holds

$$|x \top y - \text{RZ}(x \top y)| \leq \beta^{1-p} \min(x \top y, \text{RZ}(x \top y)). \quad (6)$$

Proposition 3 guarantees a bound of error after operation and rounding depending on two numbers when overflow and underflow is not occurred. However if *normal form*  $x$  and  $y$  are not chosen, rounding after  $p$ -digit loss a lot of precision and Proposition 3 is useless. For instance, take  $x = 0.1 \cdot 10^1$  in  $(10, 2, 0, 2)$  floating-point system. When  $x^2 = 0.01 \cdot 10^2$  is rounded down on second digit, the result is not equal  $\text{RZ}(x^2) = x$  and its error is 1 larger than  $2^{-1}$  calculated from (6).

The IEEE Standard [28] introduces  $(2, 24, -2^7 + 2, 2^7 - 1)$  and  $(2, 53, -2^{10} + 2, 2^{10} - 1)$  floating-point number systems, which are also called single and double precision, respectively. In this paper, analog of those number system will be homomorphically implemented in Section 5 and simulated in Section 7.

<sup>3</sup> We do not distinguish the definition of *normal form* and *subnormal form* in [26].

### 3 Floating-point encryption and decryption

In this section, floating-point encryption and decryption are constructed, which will be used for constructing FPFHE.

#### 3.1 Floating-point encoding and decoding

We propose encoding and decoding algorithm between floating-point numbers and the corresponding message polynomials. We choose  $q \in \mathbb{N}$  and *shared primes*  $Q_0 = \nu 2^{n_0} + 1$  and  $Q_1 = \nu 2^{n_1} + 1$  with  $Q_0 > Q_1$ , and define scaling factor  $\Delta = Q_1$  and  $\Delta' = \Delta 2^q \nu$  and  $\beta$ -evaluation map  $\Psi_\beta : \mathbb{N}[X] \rightarrow \mathbb{Q}$ ,  $a(X) \mapsto a(\beta)\beta^{1-p}$ . Then for a given *normal form*  $(s, m, e)$  of floating point number  $x$ , **Encode** and **Decode** are defined as follows:

- **Encode** $(s, m = (m_{p-1}.m_{p-2} \dots m_0)_\beta, e)$ 
  - For the sign  $s$ , set a the polynomial  $M^s(X) \triangleq \Delta s$ .
  - For the fraction  $m$ , set the fraction polynomial  $M^f(X) \triangleq \Delta \sum_{i=0}^{p-1} m_i X^i$ .
  - For the exponent  $e$ , set the exponent polynomial  $M^e(X) \triangleq \Delta' e$ .
  - Return  $(M^s(X), M^f(X), M^e(X))$ .
- **Decode** $(M^s(X), M^f(X), M^e(X))$ 
  - Set  $s = 1$  if  $M_0^s > 0$ ,  $s = -1$  otherwise.
  - Calculate  $a(X) = \left\lfloor \left( M^f(X) + \lfloor \Delta/2 \rfloor \right) / \Delta \right\rfloor$  and set  $m = \Psi_\beta(a(X))$ .
  - Set  $e = \left\lfloor \left( M_0^e + \lfloor \Delta'/2 \rfloor \right) / \Delta' \right\rfloor$ .
  - Return  $s \cdot m \cdot \beta^e$ .

Note that after analyzing bootstrapping error in Section 4.2, following facts are obtain: (i) The size of  $Q_1$  controls bootstrapping error. (ii) Rounding error after doing tensor product of two MLWE ciphertexts are relatively small when  $Q_0$  and  $Q_1$  are *shared primes*. Moreover, the size of  $Q_0 > Q_1$  is determined depending on  $\beta$ ,  $p$ , and carry system, analyzed in Section 5.2. The  $q$  is also used to integer modulus of LWE ciphertext and *shared primes* are found by exhaustive search.

Since evaluation map  $\Psi_\beta$  is a homomorphism-like map as

$$\begin{aligned} \Psi_\beta(M^{f,1}(X) + M^{f,2}(X)) &= \Psi_\beta(M^{f,1}(X)) + \Psi_\beta(M^{f,2}(X)), \\ \Psi_\beta(M^{f,1}(X) \cdot M^{f,2}(X)) &= \Psi_\beta(M^{f,1}(X)) \cdot \Psi_\beta(M^{f,2}(X))\beta^{1-p}, \end{aligned}$$

for given fraction polynomials  $M^{f,1}(X)$  and  $M^{f,2}(X)$ , MLWE ciphertext having fraction message polynomial can perform leveled homomorphic operations. However, these relation is not hold on the quotient polynomial ring  $R_{N,Q}$  when an one of coefficient or degree of result exceeds its integer or polynomial modulus. This problem will be resolved and fully homomorphic operations will be obtain in Section 5.

### 3.2 Floating-point encryption and decryption schemes

In this section, a floating-point encryption scheme is proposed. We adopt the state-of-the-art TFHE cryptosystem having tensor product [15] and change its torus modulus to *shared primes*. To product two MLWE ciphertexts,  $K(K+1)/2$  evaluation keys having message  $sk_i(X)sk_j(X)$  for some  $0 \leq j \leq i \leq K-1$  and MLWE secret key  $\mathbf{sk}$  are required.

For clear expression of those indexes, following index function is used. Let  $\theta : \{(i, j) \in \mathbb{N}^2 | x \geq y\} \rightarrow \mathbb{N}$ ,  $(i, j) \mapsto i(i+1)/2 + j$  be a bijection function which is counting indexes of lower triangular of a matrix from left-top first, and  $\theta^{-1}$  be its inverse function and  $\theta_1^{-1}, \theta_2^{-1}$  be coordinate functions of  $\theta^{-1}$  such that  $\theta^{-1}(x) = (\theta_1^{-1}(x), \theta_2^{-1}(x))$ .

Given  $Q_0, Q_1$ , and  $q$ , proposed floating-point encryption scheme is given as follows:

- **Setup**( $1^\lambda$ ) Given security parameter  $\lambda$ , generate follow items:
  - Choose  $N_{\text{gct}}$  and  $K_{\text{gct}}$  for GSW,  $n$  and  $K_{\text{ct}}$  for MLWE,  $n$  for LWE ciphertext, and  $t$  for message space  $\mathbb{Z}_{2^t}$  of LWE ciphertext. Choose  $h$  for sparsity of secret key.
  - Choose gadget parameters  $B_{\text{bl}}, B_{\text{pack}}, B_{\text{ten}}$ , and  $B_{\text{ks}}$  with  $B_*/2$ -quality and  $B_*/2$ -precision,  $l_* = \lceil \log Q / \log B_* \rceil - 1$  for all  $* \in \{\text{bl}, \text{pack}, \text{ten}, \text{ks}\}$ .
- **KeyGen**( $1^\lambda$ ) Given security parameter  $\lambda$ , generate following keys:
  - Two ternary MLWE keys  $\mathbf{sk-bl}$ ,  $\mathbf{sk}$  and  $h$ -sparse LWE keys  $\mathbf{sk-ks}$ .
  - $\text{KS}_{i,j,k} = \text{ct}[sk_{i,j}B_{\text{ks}}^{k+1}]$  by using  $\mathbf{sk-ks}$  for all  $(i, j, k) \in [K_{\text{ct}}, n, l_{\text{ks}}]$ .
  - $\text{BL}_i^1 = \text{GCT}[m_i]$  and  $\text{BL}_i^{-1} = \text{GCT}[m'_i]$  by using  $\mathbf{sk-bl}$  for  $i \in [n]$  where  $(m_i, m'_i) = (1, 0)$  if  $sk-ks_i = 1$ ,  $(m_i, m'_i) = (0, 1)$  if  $sk-ks_i = -1$ ,  $(m_i, m'_i) = (0, 0)$  otherwise.
  - $\text{P}_{i,j,k} = \text{CT}[sk-bl_{i,j}B_{\text{pack}}^{k+1}]$  by using  $\mathbf{sk}$  for all  $(i, j, k) \in [K_{\text{gct}}, N_{\text{gct}}, l_{\text{pack}}]$ .
  - $\text{Ten}_{i,j} = \text{CT}[sk_{i_1}(X)sk_{i_2}(X)B_{\text{ten}}^{k+1}]$  by using  $\mathbf{sk}$  for all  $(i, j) \in [(K_{\text{ct}} + 1)K_{\text{ct}}/2, l_{\text{ten}}]$ , where  $i_1 = \theta_1^{-1}(i)$  and  $i_2 = \theta_2^{-1}(i)$ .

Set a public key as  $ev = (\mathbf{P}, \mathbf{BL}^1, \mathbf{BL}^{-1}, \mathbf{KS}, \mathbf{Ten})$  and a secret key as  $\mathbf{sk}$ .
- **Enc** $_{\mathbf{sk}}(x)$  :
  - Choose *normal form*  $(s, m, e)$  of  $x$  and run  $\text{Encode}(e, m, s)$ .
  - Return  $(\text{CT}_{\text{sign}}[M^s(X)], \text{CT}_{\text{frac}}[M^f(X)], \text{CT}_{\text{exp}}[M^e(X)])$  by using  $\mathbf{sk}$ .
- **Dec** $_{\mathbf{sk}}(\text{CT}_{\text{sign}}, \text{CT}_{\text{frac}}, \text{CT}_{\text{exp}})$  :
  - Run the  $\varphi_{\mathbf{sk}}$  for all inputs and get  $M^s(X)$ ,  $M^f(X)$ , and  $M^e(X)$ .
  - Return  $\text{Decode}(M^s(X), M^f(X), M^e(X))$ .

The proposed encryption scheme is analogous to [15] however, we adopt  $h$ -sparse secret key for encryption key-switching key, which will be used to control errors after bootstrapping. Moreover when  $Q$  is larger than  $2^{64}$ ,  $G^{-1}$  suffers a slowdown due to using high precision integer arithmetic. Next section introduces accelerating gadget decomposition on such modulus  $Q$ .

---

**Algorithm 1**  $c \leftarrow G_{\text{crt}}^{-1}(\mathbf{d})$ , accelerating gadget decomposition on CRT

---

**Input:**  $Q_0 = \nu 2^{\eta_0} + 1$ ,  $Q_1 = \nu 2^{\eta_1} + 1$ ,  $\mathbf{d} = (a_1, b_1) \times \dots \times (a_n, b_n) \in (\mathbb{Z}_{Q_0} \times \mathbb{Z}_{Q_1})^n$

**Output:**  $c = (c_{0,0}, c_{0,1}, \dots, c_{0,l-1}, c_{1,0}, \dots, c_{1,l-1}, \dots, c_{n-1,w}) \in \mathbb{Z}_Q^{1 \times nl}$

```

1: calculate  $\hat{Q}_1 = Q_0^{-1} \pmod{Q_1}$  ▷ Without loss of generality,  $Q_1 \leq Q_0$ 
2: for  $i \in [n]$  do
3:    $x = (a_i - b_i)\hat{Q}_1 \pmod{Q_1}$ 
4:    $y = x + b_i \pmod{2^{\eta_0}}$ 
5:    $z = x\nu + \lfloor (x + b_i)/2^{\eta_0} \rfloor$ 
6:    $c_i = (c_{i,0}, \dots, c_{i,l-1}) := G^{-1}(y + 2^{\eta_0}z)$  ▷ Guarantee that  $0 \leq y < 2^{\eta_0}$ 
7: end for
8: return  $c = (c_1, \dots, c_n)$ 

```

---

### 3.3 Accelerating gadget decomposition on shared primes

Let gadget decomposition  $G^{-1}$  from Proposition 2 is given. To avoid using arithmetic operation larger than 64-bit, we save every element  $x$  as a CRT form as (1) and Algorithm 1, denoted as  $G_{\text{crt}}^{-1}$ , is used.

The correctness of  $G_{\text{crt}}^{-1}$  is from the following property. For any  $(a, b) \in \mathbb{Z}_{Q_0} \times \mathbb{Z}_{Q_1}$  with  $0 \leq a < Q_0$ ,  $0 \leq b < Q_1$ , and  $c = \phi^{-1}(a, b)$ , there exists  $x < Q_0$  such that  $c = b + xQ_1 = (b + x) + (x\nu 2^{\eta_0})$ . Since  $Q_1 \leq Q_0$ ,  $\phi^{-1}(b, b) = b$ , hence we obtain

$$xQ_1 = \phi^{-1}(a, b) - \phi^{-1}(b, b) = \phi^{-1}(a - b, 0) = (a - b)Q_1\hat{Q}_1,$$

which means  $x = (a - b)\hat{Q}_1 \pmod{Q_0}$ . Then we can split  $c \in \mathbb{Z}_Q$  into lower significant  $\eta_0$ -bit and more significant  $\eta_1$ -bit without calculating exact value of  $c$ , and run gadget decomposition twice, by using 64-bit integer operations.

## 4 Error analysis with deterministic gadget decomposition and sequential bootstrapping for FHE

In this section, we revisit error analysis of bootstrapping [15] and propose sequential bootstrapping on *shared primes*. Section 4.1 proves more generalized result of previous work [10], which is used to analyze error amplification without independent heuristic even when deterministic gadget decomposition is used.

Section 4.2 performs an error analysis for the product of two fraction ciphertexts following case, which is the worst case of constructing fully homomorphic operations in Section 5. Assume that *valid squashed* two ciphertexts  $\mathbf{ct}_i^1$  and  $\mathbf{ct}_i^2$  having  $i$ -digit fraction messages are given for all  $i \in [p]$ . Then following algorithms are run: (i) A **BlindRotate** in Algorithm 2 runs to reduce error and raise modulus from  $q$  to  $Q$ ; (ii) A **Packing** in Algorithm 13 runs to pack outputs of **BlindRotate** into two MLWE ciphertexts  $\text{CT}_1$  and  $\text{CT}_2$ ; (iii) A **TensorProd** in Algorithm 14 runs to product  $\text{CT}_1$  and  $\text{CT}_2$ , and  $p$  LWE ciphertexts  $(\mathbf{ct}'_i)_{i \in [p]}$  are obtained by using **SampleExtract**. (iv) A **KeySwitch** in Algorithm 3 runs to generate *squashed* LWE ciphertext from  $(\mathbf{ct}'_i)_{i \in [p]}$ .

If the results of above process are *valid* ciphertexts, a server can rerun this process a polynomial number of times. Note that this process is analogous to **PackedSumProducts** in [15], however we use **KeySwitch** to reduce ring and integer modulus of ciphertext after doing tensor product.

However after multiplying two fraction message polynomials having degree  $p - 1$ , the  $p - 1$  coefficient can have a large message bit than  $2^t$ . To solve this problem, Section 4.3 introduces a sequential bootstrapping.

#### 4.1 Investigation of subgaussian random variables having Pythagorean additivity

For subgaussian random variables  $X$  and  $Y$ , Corollary 1 requires boundedness of both  $X$  and  $Y$  to show that  $XY$  is a subgaussian. However, we will show that it is enough to require boundedness of one of  $X$  and  $Y$  and subgaussian others as follows:

**Lemma 2.** *Let  $X$  be a  $B$ -bounded random variable and  $Y$  be a  $\sigma$ -subgaussian such that  $X$  and  $Y$  are uncorrelated, then  $XY \sim \text{subG}(\sqrt{8}B\sigma)$ .*

*Proof.* By using uncorrelated property, we obtain  $\mathbb{E}[XY] = \mathbb{E}[X]\mathbb{E}[Y] = 0$ . Since following inequality holds,

$$\mathbb{P}(|XY| > t) \leq \mathbb{P}(|Y| > t/B) \leq 2 \exp\left(-\frac{t^2}{\sigma^2 B^2}\right). \quad (7)$$

it is known fact that (i) every  $k$ -th momentum is bounded as  $\mathbb{E}[|XY|^k] \leq (2B^2\sigma^2)^{k/2} k\Gamma(k/2)$  where  $\Gamma(\cdot)$  is a gamma function and (ii) a moment function is bounded by  $M_{XY}(s) \leq \exp(4B^2\sigma^2 s^2)$  [30].  $\square$

However, the factor  $\sqrt{8}$  in Lemma 2 is undesirable and if we can use somewhat more information of  $Y$  is given,  $\sqrt{8}$  is removed as follows:

**Lemma 3.** *Let  $X$  be a  $B$ -bounded random variable and  $Y$  be a  $\sigma$ -subgaussian with a symmetric distribution, i.e.  $\mathbb{E}[Y^{2n-1}] = 0$  for all  $n \in \mathbb{N}$ , If both  $X$  and  $Y$  are independent, then  $XY \sim \text{subG}(B\sigma)$ .*

*Proof.* By using independent property, we obtain  $\mathbb{E}[XY] = \mathbb{E}[X]\mathbb{E}[Y] = 0$ . By Lemma 2, there exists a measurable function pointwisely larger than the moment function  $M_{XY}(s)$  for all  $s \in \mathbb{R}$ . Then for any  $s \in \mathbb{R}$ ,

$$\begin{aligned} M_{XY}(s) &= \int_{\Omega} e^{sXY} d\mathbb{P} = \int_{\Omega} \lim_{m \rightarrow \infty} \sum_{n=1}^m \frac{(sXY)^n}{n!} d\mathbb{P} \stackrel{(a)}{=} \lim_{m \rightarrow \infty} \sum_{n=1}^m \int_{\Omega} \frac{(sXY)^n}{n!} d\mathbb{P} \\ &\stackrel{(b)}{\leq} \lim_{m \rightarrow \infty} \sum_{n=1}^m \int_{\Omega} \frac{(sB)^{2n} Y^{2n}}{2n!} d\mathbb{P} \stackrel{(c)}{=} M_{BY}(s) \stackrel{(d)}{\leq} \exp\left(\frac{(\sigma B)^2 s^2}{2}\right), \end{aligned} \quad (8)$$

where (a) holds from monotone convergence of measurable functions with boundedness of  $M_{XY}(s)$  [9], (c) holds from the property that  $Y$  has a symmetric distribution, and (d) holds from the property of  $B$ -scaled subgaussian. In addition,

(b) holds since odd momentum of  $\mathbb{E}[(XY)^{2n+1}] = \mathbb{E}[X^{2n+1}] \cdot \mathbb{E}[Y^{2n+1}]$  is zero for all  $n \in \mathbb{N}$  by using independent property, and even momentum is bounded by Lebesgue integral property with  $Y^{2n} \leq B^{2n}$  [9] for all  $n \in \mathbb{N}$ .  $\square$

Then, we can derive the following corollary based on Lemma 1 and 3.

**Corollary 2.** *Let  $Y_i \sim \text{subG}(\sigma)$  be mutually independent random variables having symmetric distribution for all  $i \in [n]$ . Let  $X_1, \dots, X_n$  be  $B$ -bounded random variables where  $X_i$  is dependent only for all  $X_0, Y_0, \dots, X_{i-1}$ , and  $Y_{i-1}$ . Then  $X_0Y_0, \dots, X_{n-1}Y_{n-1}$  have Pythagorean additivity. .*

*Proof.* By using Lemma 3,  $Z_i = X_iY_i$  are  $\text{subG}(\sigma B)$  random variables for all  $i \in [n]$ . Since  $Y_i$  is independent to all  $Z_1, \dots, Z_{i-1}$  and  $X_i$  is still  $B$ -bounded even if  $Z_1, \dots, Z_{i-1}$  are given, therefore  $X_0Y_0, \dots, X_{n-1}Y_{n-1}$  have *Pythagorean additivity* by using Lemma 2.  $\square$

Note that Corollary 2 does not require  $X$  to have subgaussian property, meaning that  $\mathbb{E}[X]$  can not be equal to zero compared to previous Corollary 1. Most of additional errors after running bootstrapping are formed of product of output of gadget decomposition and error in ciphertext or secret key. Since statistics of deterministic gadget decomposition relies on its input, many case of expectation of output is not zero, which is suitable for applying Corollary 2.

## 4.2 Error analysis: after running **BlindRotate**, **Pack**, **TensorProd**, and **KeySwitch** algorithms

In this section, four algorithms **BlindRotate**, **Packing**, **TensorProd**, and **KeySwitching** are run sequentially and error analysis for the output of each algorithms is performed. Since these algorithms have been widely studied in FHE with GINX-bootstrapping [13, 15], these algorithms are provided in Supplementary material except **BlindRotate** and **KeySwitch** which are modified to properly operate the proposed OD-FPFHE. Moreover, result of error analysis is given in this section and detailed proofs is provided in Supplementary material.

First, we analyze **BlindRotate**. Assume that a *squashed ct* and  $\text{ACCPoly}(X)$  are given which determine the output message as in (4). First, the blind rotation in [23] is modified to Algorithm 2 and error analysis is performed as in Lemma 4. Note that **BlindRotate** returns  $2^c$  LWE ciphertexts by using **SampleExtract** in (2) where  $c$  is pre-determined when **ct** is generated by running **KeySwitch** which is defined below.

The difference between Algorithm 2 and blind rotation in [23] is Line 3, where [23] runs with following equation  $\text{ACC}+ = [(X^{a_i} - 1)\text{ACC} \boxtimes \text{BL}_i^1] + [(X^{-a_i} - 1)\text{ACC} \boxtimes \text{BL}_i^{-1}]$ . To calculate external product  $\boxtimes$ , gadget decomposition should be run as  $G_{\text{crt}}^{-1}((X^{a_i} - 1)\text{ACC})$  and  $G_{\text{crt}}^{-1}((X^{a_i} + 1)\text{ACC})$ . However, in Algorithm 2, only  $G_{\text{crt}}^{-1}(\text{ACC})$  calculation is required.

Such difference gives more impact in the complexity when **ct** is encrypted by using secret key having a support larger than ternary case. Suppose that secret

---

**Algorithm 2**  $\text{out} \leftarrow \mathbf{BlindRotate}(\mathbf{ct}, \text{ACCPoly}(X), ev)$

---

**Input:**  $\mathbf{ct} = (a_1, \dots, a_n, b) \in \mathbb{Z}_{2N_{\text{gct}}}^{n+1}$ ,  $\text{ACCPoly}(X) \in R_{N_{\text{gct}}, Q}$

**Output:**  $\text{out} \in \mathbb{Z}_Q^{(N_{\text{gct}}K_{\text{gct}}+1) \times 2^c}$

- 1:  $\text{ACC} := (0(X), \dots, 0(X), X^{-b} \text{ACCPoly}(X)) \in R_Q^{k+1}$
  - 2: **for**  $i \in [n]$  **do**
  - 3:      $\text{ACC} += (X^{a_i} - 1)[\text{ACC} \boxtimes \text{BL}_i^1] + (X^{-a_i} - 1)[\text{ACC} \boxtimes \text{BL}_i^{-1}]$
  - 4: **end for**
  - 5: **return**  $\text{out} = (\mathbf{SampleExtract}(\text{ACC}, \alpha))_{\alpha \in [2^c]}$
- 

key having the support  $\{d_0, \dots, d_{m-1}\}$  and  $\text{BL}_i^j$  is encrypted with message 1 if  $s_i = d_j$ , and 0 otherwise for  $(i, j) \in [n, m]$ . Then Line 3 of **BlindRotate** is replaced by following operation

$$\text{ACC} += \sum_{(i,j) \in [n,m]} (X^{a_i d_j} - 1)[\text{ACC} \boxtimes \text{BL}_i^j]. \quad (9)$$

Since only  $G_{\text{crt}}^{-1}(\text{ACC})$  is used to perform  $\boxtimes$  for all index  $j$  in (9), only a number of  $(K_{\text{gct}} + 1)l_{\text{bl}} + 1$  NTT operations are required and up to double errors are added compared to previous result [23].

Next, an error amplification of **BlindRotate** is analyzed as follows:

**Lemma 4.** *Assume that Algorithm 2 runs with valid squashed  $\mathbf{ct}$ , and returns  $\text{out}_\alpha \in \mathbb{Z}_Q^{N_{\text{gct}}K_{\text{gct}}+1}$  for the message  $(\text{ACCPoly}(X) X^{-\varphi(\mathbf{ct})})_\alpha$ . Then for any  $\alpha \in [N_{\text{gct}}]$ , the error  $\alpha$ -coefficient error  $\mathcal{E}_{\text{bl}}^{(\alpha)}$  of  $\text{out}_\alpha$  is bounded except with probability  $2^{-\Omega(v)}$  as follows:*

$$|\mathcal{E}_{\text{bl}}^{(\alpha)}| = O\left(B_{\text{bl}} \sqrt{v N_{\text{gct}} K_{\text{gct}}} \left(n + \sigma \sqrt{n l_{\text{bl}}}\right)\right). \quad (10)$$

Proof is listed in Supplementary material.

Second, we analyze **Packing**  $p$  ciphertexts obtained by **BlindRotate** are packed into one ciphertext by **Packing** which generates  $\text{CT}_{\text{frac}}$ . Since **Packing** has been widely used and studied in FHEs [11, 23, 13], it is provided as Algorithm 13 in Supplementary material. An error amplification of **Packing** after running **BlindRotate** is analyzed in Lemma 5.

**Lemma 5.** *Assume that Algorithm 13 runs with  $p$  ciphertexts  $(\mathbf{ct}_i[\Delta m_i])_{i \in [p]}$  where  $\mathbf{ct}_i \in \mathbb{Z}_Q^{N_{\text{gct}}K_{\text{gct}}+1}$  are generated by running Algorithm 2 with valid squashed  $(\mathbf{ct}'_j)_{j \in [p]}$ , and returns a ciphertext  $\text{OUT}[\Delta \sum_{i \in [p]} m_i X^i] \in R_{N_{\text{ct}}, Q}^{K_{\text{ct}}+1}$ . Then for any coefficient  $\alpha \in [2p]$ , the  $\alpha$ -coefficient error  $\mathcal{E}_{\text{pack}}^{(\alpha)}$  of  $\text{OUT}$  is bounded except with probability  $2^{-\Omega(v)}$  as follows:*

$$|\mathcal{E}_{\text{pack}}^{(\alpha)}| = |\mathcal{E}_{\text{bl}}^{(\alpha)}| + O\left(B_{\text{pack}} \sqrt{v N_{\text{gct}} K_{\text{gct}}} (p + \sigma \sqrt{l_{\text{pack}} p})\right). \quad (11)$$

Proof is listed in Supplementary material.

Third, we analyze **TensorProd** Two ciphertexts packed from **Packing** are multiplied by using **TensorProd**. Since **TensorProd** have been widely used and studied in FHEs [11, 15], it is listed as Algorithm 14 in Supplementary material.

An error amplification of **TensorProd** after running **BlindRotate** and **Packing** is analyzed in Lemma 6.

**Lemma 6.** *Assume that Algorithm 14 runs with two ciphertexts  $\text{CT}_1[m_1(X)]$  and  $\text{CT}_2[m_2(X)] \in R_{N_{\text{ct}}, Q}^{K_{\text{ct}}+1}$  which are generated by running Algorithm 2 and 13 with valid squashed  $(\text{ct}_j)_{j \in [p]}$  and  $(\text{ct}'_j)_{j \in [p]}$ , and returns  $\text{OUT}[\Delta^2 m_1(X) m_2(X)] \in R_{N_{\text{ct}}, Q}^{K_{\text{ct}}+1}$ . If  $\Delta = \Omega(N_{\text{ct}} |\mathcal{E}_{\text{pack}}|)$  is chosen and both coefficient of  $m_1(X)$  and  $m_2(X)$  are bounded by  $\Delta(\beta - 1)$ , respectively, then for any  $\alpha \in [2p]$ , the  $\alpha$ -coefficient error  $\mathcal{E}_{\text{Ten}}^{(\alpha)}$  of  $\text{OUT}$  is bounded except with probability  $2^{-\Omega(v)}$  as follows:*

$$|\mathcal{E}_{\text{ten}}^{(\alpha)}| = O\left(\Delta p \beta \left| \mathcal{E}_{\text{pack}}^{(p-1)} \right| + K_{\text{ct}}^2 N_{\text{ct}}^2 l_{\text{ten}} B_{\text{ten}} + \sigma B_{\text{ten}} K_{\text{gct}} \sqrt{v l_{\text{ten}} N_{\text{gct}}}\right) \quad (12)$$

Proof is listed in Supplementary material.

Finally, we analyze **KeySwitch** After two ciphertexts are multiplied by **TensorProd** and **SampleExtract** for some coefficient  $\alpha \in [2p]$ , the result is *squashed* by **KeySwitch**. For a while, the message of *squashed ct* has the formed of  $m\Delta^2$ , where  $m = (m_{t'-1} \dots m_1 m_0)_{(2)}$  and  $m_{f-1} = \dots = m_1 = m_0 = 0$  for given  $f \in [t']$ . The goal of **KeySwitch** is to bootstrap the following  $s$  bits  $(m_{f+s-1} \dots m_{f+1} \dots m_f)_{(2)}$  after  $0$ 's and to return  $2^c$  outputs[15] after running **BlindRotate**. The above assumption will be resolved in next section.

---

**Algorithm 3 out**  $\leftarrow$  **KeySwitch**(CT,  $l$ ,  $s$ ,  $c$ ,  $ev$ )

---

**Input**  $\text{ct}[m\Delta^2] \in \mathbb{Z}_Q^{K_{\text{ct}} N_{\text{ct}}+1}$ , start index  $f$ , a number of desirable bootstrapping bit  $s$  and the number of multi-out bit  $c$ .

**Output** *squashed out*  $[(m_{f+s} \dots m_f)_{(2)} 2^{\log N_{\text{gct}} - s}] \in \mathbb{Z}_{2^n}^{n+1}$

- 1:  $\text{CT} \leftarrow \lfloor \text{CT} \rfloor_{Q \rightarrow Q_0 \approx \nu 2^{n_0}}$
  - 2: Calculate the bias  $= 2^{f-1} \nu$  and add it to  $b$  of  $\text{CT}$ .
  - 3:  $\text{CT} \leftarrow \lfloor \text{CT} / \nu 2^{n_1 + s + c + 1 + f - q} \rfloor \bmod 2^q$
  - 4: Set  $\text{out} = (0, 0, \dots, 0, b_{\text{ct}}) \in \mathbb{Z}_{2^q}^{K_{\text{ct}} n + 1}$   $\triangleright$  where  $b_{\text{ct}}$  is  $b$  of  $\text{CT}$
  - 5: **for**  $(j, x) \in [K_{\text{ct}}, n]$  **do**
  - 6:  $v = G^{-1}(a_{\text{ct}, j})$   $\triangleright$  where  $a_{\text{ct}, j}$  is the  $j$ -coefficient of  $a$  of  $\text{CT}$
  - 7:  $\text{out} += \sum_k v_k \text{KS}_{j, x, k}$
  - 8: **end for**
  - 9: **return out**  $\leftarrow \lfloor \text{out} / 2^{q-1 - \log N_{\text{gct}}} \rfloor 2^c \bmod 2N_{\text{gct}}$
- 

**Lemma 7.** *Assume that Algorithm 3 runs with a ciphertext  $\text{ct}[m\Delta^2]$  generated by running Algorithm 2, 13, 14, and **SampleExtract** with valid squashed  $(\text{ct}_j)_{j \in [p]}$  and  $(\text{ct}'_j)_{j \in [p]}$ . If message  $m = (m_{t'-1} \dots m_0)_{(2)}$  with  $m_{f-1} = \dots =$*

$m_0 = 0$  is given and  $\Delta = \Omega(N_{\text{ct}}|\mathcal{E}_{\text{pack}}|)$ , then the error of **out** with message  $(m_{f+s}\dots m_s)_{(2)}2^{\log N_{\text{gct}}-s}$  is bounded except with probability  $2^{-\Omega(v)}$  as

$$O\left(\frac{|\mathcal{E}_{\text{ten}}^{(p-1)}| + \Delta\nu p\beta^2}{\Delta\nu 2^{f+\eta_1+s-\log N_{\text{gct}}}} + \frac{\sigma B_{\text{ks}}\sqrt{N_{\text{ct}}K_{\text{ct}}v}}{2^{q-1-\log N_{\text{gct}}}} + \sigma\sqrt{hv}\right) \quad (13)$$

Proof is listed in Supplementary material.

If (13) is less than or equal  $2^{2\log N_{\text{gct}}-t}$ , output of **KeySwitch** is *valid* ciphertext and hence **BlindRotate** can be applied again. From now on, We will call that a proposed floating-point encryption is *valid* if parameters satisfy those inequality with  $f = 0$ ,  $c = 0$  and  $s = t - 1$ .

Moreover if *shared primes* are used, messages and approximated modulus  $\nu 2^{\eta_0}$  after running Line 1 in **KeySwitch** share same scaling factor  $\nu$  with negligible error amplification. This property enables to change from calculating denominator in Line 3 to shifting  $\nu$  without extra message deformation.

In addition, if a non-sparse ternary secret is used key for encrypting  $\text{KS}_{j,x,k}$ , the third error term of (13) becomes  $O(\sigma\sqrt{nv})$ . Although the first and second error terms of (13) can be reduced by changing  $\Delta = Q_1$  and  $q$ ,  $O(\sigma\sqrt{nv})$  cannot be controlled hence makes an error floor. However if a sparse ternary secret key is used for  $\text{KS}_{j,x,k}$ , this error term is controlled by a sparsity  $h$ .

### 4.3 Sequential bootstrapping for accommodating large numbers

In this section, we discuss a methodology to bootstrap a ciphertext for a large message bit based on the error analysis Lemma 4-7. We recall that WoP-PBS algorithm in [15] enables bootstrapping and moreover returns correct ciphertext even when MSB of message in a *squashed* ciphertext is one. Analogously, we will explain how to construct WoP-PBS on integer modulo product  $Q$  which is product of *shared primes* by using the following **ACCPoly 1**.

**ACCPoly 1:** Used to WoP-PBS, with  $c = 1$ ,  $s = 4$ , and  $f = 0$

output \ location	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1st outputs ( $\times\Delta$ )	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
2st outputs ( $\times\Delta$ )	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1

To instantiate WoP-PBS on *shared primes*, assume that a ciphertext  $\text{ct}[m\Delta^2]$  with  $m = (m_t\dots m_1m_0)_{(2)}$  is given which is generated by running Algorithms 2 and 13, then extracted by using **SampleExtract**, and assume that the message space of LWE ciphertext is  $\mathbb{Z}_{2^t} = \mathbb{Z}_{2^6}$ . Although a *valid* floating-point encryption is given and Algorithm 3 runs with  $f = 0$  and  $s = 4$ , output of **BlindRotate** is sign-reversed by when  $m_4 = 1$  in (4).

Then the  $\text{ACCPoly}(X)$  constructed from **ACCPoly 1** is used to fix its sign. Let  $\text{ot}_1$  and  $\text{ot}_2$  be output functions of **ACCPoly 1** with the inputs  $0, \dots, 15$ .

Then, the the ACC initial polynomial  $\text{ACCPoly}(X) = \sum_{i \in [N_{\text{gct}}]} (a_i + b_i) X^i$  is defined as follows: If  $i$  is even, then set  $a_i = \text{ot}_1(\lfloor i * 2^s / N_{\text{gct}} \rfloor) \Delta$  and  $b_i = 0$ , otherwise, set  $a_i = 0$  and  $b_i = \text{ot}_2(\lfloor i * 2^s / N_{\text{gct}} \rfloor) \Delta = \Delta$ .

After running **BlindRotate** with **ACCPoly 1**, we obtain two ciphertexts  $\text{CT}_1[(-1)^{m_4} \Delta (m_3 m_2 m_1 m_0)_{(2)}]$  and  $\text{CT}_2[(-1)^{m_4} \Delta]$ . Finally, if four main algorithms run again with two ciphertexts and **ACCPoly 1**, *valid* ciphertext  $\text{CT}'[(m_3 m_2 m_1 m_0)_{(2)} \Delta]$ . This is the application of WoP-PBS in our *shared primes*.

**ACCPoly 2:** Used to sequential bootstrapping, with  $c = 1$ ,  $s = 4$ , and  $f = 0$

output \ location	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1st outputs ( $\times \Delta$ )	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
2st outputs ( $\times \Delta^2$ )	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15

However to bootstrap next 4-bits  $(m_7 m_6 m_5 m_4)_{(2)}$  message, lower significant 4-bits should be removed from  $\text{ct}[m \Delta^2]$ . This can be done by replacing the second used **ACCPoly 1** above process to **ACCPoly 2**. Since error  $|\mathcal{E}_{\text{ten}}(X)|$  is  $Q_1$  times larger than  $|\mathcal{E}_{\text{pack}}(X)|$  in Lemma 5 and 6, subtracting or adding ciphertexts generated from second output of **ACCPoly 2** from a  $\text{ct}$  still *valid* as many  $\text{poly}(\eta_1)$ -times. Therefore after subtraction, we obtain  $\text{ct}'[\Delta (m_{t'} \dots m_6 m_5)_{(2)}]$  hence **KeySwitch** can run with  $\text{ct}'$  correctly. Finally we proposes a sequential bootstrapping from above observation.

**Theorem 1 (sequential bootstrapping, analogous of Lemma 5 of [15]).** *Let valid floating-point encryption scheme with LWE message space  $\mathbb{Z}_{2^t}$  for  $t \geq 2$  is given. Then for every message bits  $m_i$  of ciphertext  $\text{ct}[(m_{t-1} \dots m_0)_{(2)} \Delta^2]$  returned from running Algorithm 2, 13, 14, and **SampleExtract** and for any scaling  $\Delta'' \geq \Delta$ , a valid ciphertext  $\text{CT}[m_i \Delta'']$  can be generated.*

Although Theorem 1 is similar to Lemma 5 in [15], NTT algorithm can be used in the proposed floating-point encryption, and hence having a large messages are possible without generating extra noise contrast to using FFT.

In the next section, homomorphic addition and multiplication algorithms are introduced for the proposed floating-point.

## 5 Overflow-detectable floating-point FHE

In this section, we propose an overflow-detectable floating-point FHE. Section 5.1 proposes two homomorphic arithmetic operations **ADD** and **MULT**. Section 5.2 constructs various homomorphic algorithms which are important subroutines for **ADD** and **MULT**. Section 5.3 proposes a homomorphic normalization method for the floating-point outputs. Finally, Section 5.4 introduces a homomorphic algorithms for generating ciphertext with the message indicating overflow occurrence.

Due to Theorem 1, various floating-point homomorphic operations can be constructed and we implement (4,27,-511,511) and (4,12,-127,127) floating-point FHE as examples, which achieve double and single precision, respectively. Also, we choose LWE message space parameter  $t = 6$  for bootstrapping each 5-bit of message by using WoP-PBS. After explaining each pseudo-code of homomorphic algorithms in Section 5.2, various ACC initial polynomials used to implement those algorithms are introduced with (4,27,-511,511) floating-point FHE and  $t = 6$ .

### 5.1 Overview of homomorphic operations for OD-FPFHE: addition, multiplication and overflow-detection

A homomorphic addition of two floating-point ciphertexts is proposed in Algorithm 4, denoted as **ADD**. Note that before adding two fraction ciphertexts, both exponents should be equal. Lines 1-5 show the process of equalizing both exponents. Also, subtraction can be easily constructed by replacing  $+$  to  $-$  in Line 6 of Algorithm 4.

---

**Algorithm 4 :**  $(\text{Out}_{\text{frac}}, \text{Out}_{\text{sign}}, \text{Out}_{\text{exp,proof}}) \leftarrow \mathbf{ADD}(\text{FCT}^1, \text{FCT}^2, \text{proof})$

---

**Input**  $\text{FCT}^1 = (\text{CT}_{\text{frac}}^1, \text{CT}_{\text{sign}}^1, \text{CT}_{\text{exp}}^1)$ ,  $\text{FCT}^2 = (\text{CT}_{\text{frac}}^2, \text{CT}_{\text{sign}}^2, \text{CT}_{\text{exp}}^2)$ ,  $\text{proof}$

- 1:  $\text{CT}_{\text{exp}}^{\max}[\max(m_1, m_2)\Delta'] = \mathbf{Max}(\text{CT}_{\text{exp}}^1[m_1][m_1\Delta'], \text{CT}_{\text{exp}}^2[m_2\Delta'])$
- 2: **for**  $i=1:2$  **do**
- 3:      $\text{CT}_{\text{exp}}^{\text{diff}}[\min(\max(m_1, m_2) - m_i, p)\Delta'] = \mathbf{Min}(\text{CT}_{\text{exp}}^{\max} - \text{CT}_{\text{exp}}^i, \text{CT}[p\Delta'])$
- 4:      $\text{tmpCT}_i = \mathbf{TensorProd}(\mathbf{ConstToExp}(\text{CT}_{\text{exp}}^{\text{diff}}, \text{CT}_{\text{sign}}^i), \text{CT}_{\text{frac}}^i)$
- 5: **end for**
- 6:  $(\text{Out}_{\text{sign}}, \text{Out}_{\text{frac}}, (\text{IsZero}_i)_{i \in [p]}) = \mathbf{CarryAdd}(\text{tmpCT}_1 + \text{tmpCT}_2)$
- 7:  $\text{proof}' := \mathbf{GenProof}(\text{Out}_{\text{exp}}, \text{proof})$
- 8:  $(\text{Out}_{\text{frac}}, \text{Out}_{\text{exp}}) = \mathbf{Normal}((\text{IsZero}_i)_{i \in [p]}, \text{CT}_{\text{exp}}^{\max} + 1, \text{Out}_{\text{frac}})$
- 9: **return**  $(\text{Out}_{\text{frac}}, \text{Out}_{\text{sign}}, \text{Out}_{\text{exp,proof}}')$

---

The following operations are homomorphically performed. (i) **ADD** takes two floating-point ciphertexts, and MLWE ciphertext proof with the message indicating the overflow occurrence in the previous operations; (ii) The maximum of two exponents is calculated in Line 1; (iii) The differences between each exponent and max values are calculated and cut less than  $p$  in Line 3; (iv) The difference values are sign-reversed and lifted to the monomial exponent multiplied with its sign message by **ConstToExp**, and then the outputs are multiplied with each fraction message by **TensorProd** in Line 4; (v) **CarryAdd** bootstraps each coefficient to be less than the precision  $\beta$  and moves its carry to higher coefficients.

A homomorphic multiplication is proposed in Algorithm 5, denoted as **MULT**, which takes the homomorphic calculations. (i) **MULT** takes two floating-point

---

**Algorithm 5** :  $(\text{Out}_{\text{frac}}, \text{Out}_{\text{sign}}, \text{Out}_{\text{exp}}, \text{proof}') \leftarrow \mathbf{MULT}(\text{FCT}^1, \text{FCT}^2, \text{proof})$

---

**Input**  $\text{FCT}^1 = (\text{CT}_{\text{frac}}^1, \text{CT}_{\text{sign}}^1, \text{CT}_{\text{exp}}^1)$ ,  $\text{FCT}^2 = (\text{CT}_{\text{frac}}^2, \text{CT}_{\text{sign}}^2, \text{CT}_{\text{exp}}^2)$ ,  $\text{proof}$

- 1:  $(\text{Tmp}_{\text{frac}}, (\text{IsZero}_i)_{i \in [27]}) = \mathbf{CarryMul}(\mathbf{TensorProd}(\text{CT}_{\text{frac}}^1, \text{CT}_{\text{frac}}^2))$
- 2:  $\text{Tmp}_{\text{exp}} = \text{CT}_{\text{exp}}^1 + \text{CT}_{\text{exp}}^2$
- 3:  $\text{Out}_{\text{sign}} = \mathbf{Bootstraps}$  and **Packing** with  $\mathbf{TensorProd}(\text{CT}_{\text{sign}}^1, \text{CT}_{\text{sign}}^2)$
- 4:  $\text{proof}' := \mathbf{GenProof}(\text{Out}_{\text{exp}}, \text{proof})$
- 5:  $(\text{Out}_{\text{frac}}, \text{Out}_{\text{exp}}) = \mathbf{Normal}((\text{IsZero}_i)_{i \in [p]}, \text{FCT}_{\text{exp}}^{\text{max}}, \text{Out}_{\text{frac}})$
- 6: **return**  $(\text{Out}_{\text{frac}}, \text{Out}_{\text{sign}}, \text{Out}_{\text{exp}}, \text{proof}')$

---

ciphertexts, and  $\text{proof}$ ; (ii) Fractions of two floating point numbers are multiplied by **TensorProd** in Line 1; (iii) **CarryMul** bootstraps each coefficient to be less than the precision  $\beta$  and moves its carry to higher coefficients in Line 1; (iv) Exponents of two floating point numbers are added in Line 2; (v) Signs of two floating point numbers are multiplied by **TensorProd** and bootstrapped in Line 3;

At the last part of both **ADD** and **MULT**, exponent is examined to check whether an overflow is occurs or not by **GenProof** which is explained in Section 5.4. In addition, outputs is changed into a *normal form* by **Normal** which is explained in Section 5.3. Next section will introduce homomorphic sub-algorithms for **ADD** and **MULT**.

## 5.2 Various homomorphic algorithms for ADD and MULT

We introduce sub-algorithms **Max**, **Min**, **ConstToExp**, **CarryAdd**, and **CarryMul**.

---

**Algorithm 6** :  $\text{Out} \leftarrow \mathbf{Max}(\text{CT}_{\text{exp}}^{(1)}, \text{CT}_{\text{exp}}^{(2)})$

---

- 1:  $\text{CT}_{\text{exp}}[m_e m_{e-1} \dots m_{0(2)} \Delta'] \leftarrow \text{CT}_{\text{exp}}^{(1)} - \text{CT}_{\text{exp}}^{(2)} + 2^e \Delta'$  ▷ Where  $e$  is a smallest natural number satisfying  $e_{\text{max}} - e_{\text{min}} < 2^e$ .
- 2: **for**  $i \in [e + 1]$  bit of message  $m_i$  **do**
- 3:     Generate MLWE ciphertext  $\text{CTtmp}_i[m_i \Delta]$  by using sequential bootstrapping
- 4: **end for**
- 5: **for**  $i \in [e]$  **do**
- 6:      $\text{Out} += \text{CT}[m_e m_i 2^i \Delta'] \leftarrow \mathbf{Bootstrap TensorProd}(\text{CTtmp}_e, \text{CTtmp}_i)$
- 7: **end for**
- 8: **return**  $\text{Out} + \text{CT}_{\text{exp}}^{(2)} - 2^e \Delta'$

---

First, we propose **Max** as in Algorithm 6. The correctness is followed from the equation  $\max(x, y) = \text{ReLU}(x - y) + y$  where  $\text{ReLU}(x)$  return 0 if  $x < 0$  and  $x$  otherwise. To examine the sign of message in the ciphertext  $\text{CT}_{\text{exp}}^{(1)} - \text{CT}_{\text{exp}}^{(2)}$ , we assume that both messages take values between  $e_{\text{min}}$  and  $e_{\text{max}}$  (Otherwise,

overflow flag is raised before operation. See Section 5.4). Since the magnitude of message in  $\text{CT}_{\text{exp}}^{(1)} - \text{CT}_{\text{exp}}^{(2)}$  is less than  $2^e$ , we add a  $2^e \Delta'$  and check whether  $m_e$  is still one or not by processing Line 6. Then, a ciphertext  $\text{CTtmp}_e[m_e \Delta]$  can mask other ciphertexts after running Line 7, which is same as of ReLU.

To implement and accelerate **Max** in our (4,27,-511,511) floating-point FHE and  $e = 10$ , we apply two sequential bootstrapping to generate ciphertext having 4-bit messages in Line 2. Moreover, following **ACCPoly 3** are used once to bootstrap remaining two message bits in Line 2, and we obtain two ciphertexts having message  $m_{10}(m_9 m_8 2^8 - 2^{10})$  and  $m_{10}$  at once. Note that **Min** can be implemented by equation  $\min(x, y) = -\text{ReLU}(x - y) + x$  with similar way.

**ACCPoly 3** Used for checking whether  $2^e$  is zero or not

output \ location	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
1st outputs ( $\times 2^8 \Delta'$ )	0	0	0	0	0	0	1	2	3	4	5	6	7	8	9	10	11
2nd outputs ( $\times \Delta$ )	0	0	0	0	1	1	1	1	1	1	1	1	1	1	1	1	1

Next, we propose a homomorphic algorithm lifting a constant message  $m \Delta'$  to the monomial exponent message  $\Delta X^m$  as Algorithm 7, denoted as **ConstToExp**, which is used for equalizing exponent values before addition and for normalizing after addition or multiplication. For the first case, **ConstToExp** returns ciphertext corresponding to message  $m_s \Delta X^{-m}$  for given its sign message  $m_s$ , and the last case, returns ciphertext with message  $\Delta X^m$ .

---

**Algorithm 7** : Out  $\leftarrow$  **ConstToExp**( $\text{CT}_{\text{exp}}, \text{CT}_{\text{sign}}$ )

---

**Input**  $\text{CT}_{\text{exp}}[m \Delta']$  where  $m = (m_e \dots m_0)_{(2)}$ , (*optional*)  $\text{CT}_{\text{sign}}[m_s \Delta]$

**Output** Out  $[\Delta X^m]$  where Out  $[m_s \Delta X^{-m}]$  can also be returned by packing with reversed index and multiply  $-1$  when  $i = e$  in Line 4.

- 1: Calculate ciphertexts  $\text{CT}_i[m_i \Delta]$  by using sequential bootstrapping and **Packing**
  - 2: Out  $\leftarrow \text{CT}_{\text{sign}}$  if  $\text{CT}_{\text{sign}}$  is given, Out  $= \Delta$  otherwise.
  - 3: **for**  $i \in [e + 1]$  **do**
  - 4: Out  $\leftarrow$  **TensorProd**(( $X^{2^i} - 1$ )Out,  $\text{CT}_i$ ) +  $\Delta$ Out
  - 5: Out  $\leftarrow$  **Bootstraps** Out for every index  $j \in [2^i]$  and **Packing**
  - 6: **end for**
  - 7: **return** Out
- 

The correctness of Algorithm 7 is analogous to the **BlindRotate**. Let message  $m = (m_e m_{e-1} \dots m_0)_{(2)}$  and  $\text{CT}_{\text{sign}}[m_s \Delta]$  be given. When  $i = 0$  in Line 4, Out is assigned with the message  $\Delta^2 m_s ((X - 1)m_0 + 1) = \Delta^2 m_s X^{m_0}$ . By inducting on  $i$ , Out is assigned with message  $\Delta^2 m_s X^{m_i \dots m_0(2)}$  if the previous message of Out is  $\Delta^2 m_s X^{m_{i-1} \dots m_0(2)}$ . In addition, we already know that Out in Line 4 can be bootstrapped with sufficiently large  $Q_1$  since added error of Out is relatively small by Lemma 5 and 6.

To implement and accelerate **ConstToExp** in our (4,27,-511,511) floating-point FHE, **ACCPoly 4** and **5** are used for bootstrapping in Line 2. Since the message is cut and  $m \leq p = 27 < 2^5$  is less than 5 bits, less significant 3 bits are sequentially bootstrapped by using **ACCPoly 4** and more significant 2 bits are bootstrapped by using **ACCPoly 5**. Note that a ciphertext with message  $\text{CT}[\Delta X^{32m_5+16m_4}]$  can be constructed by using **Packing** with **ACCPoly 5**. Then Algorithm 7 runs with only  $i = 0, 1, \text{ and } 2$  in Line 3 and  $\text{CT}[\Delta X^{32m_5+16m_4}]$  is multiplied, which is desired result.

**ACCPoly 4**(Left) and **5**(Right). Used for splitting constant messages

output \ location	0	1	2	3	4	5	6	7
1st outputs ( $\times \Delta$ )	0	1	0	1	0	1	0	1
2st outputs ( $\times \Delta$ )	0	0	1	1	0	0	1	1
3st outputs ( $\times \Delta$ )	0	0	0	0	1	1	1	1
4st outputs ( $\times \Delta$ )	1	1	1	1	1	1	1	1

output \ location	0	1	2	3	4	5	6	7
1st outputs ( $\times \Delta$ )	1	0	0	0	-	-	-	-
2st outputs ( $\times \Delta$ )	0	1	0	0	-	-	-	-
3st outputs ( $\times \Delta$ )	0	0	1	0	-	-	-	-
4st outputs ( $\times \Delta$ )	0	0	0	1	-	-	-	-

Next, a homomorphic carry over algorithm for addition is proposed in Algorithm 8, denoted as **CarryAdd**, which is a core part to deal with the carries occurred in addition of two fractions. Let  $\pi : \mathbb{Z} \rightarrow [\beta]$ ,  $\pi(x) = x \bmod \beta$  be a message-extraction function. After two ciphertext added, each message in coefficient should be adjusted by using  $\pi$  and remaining message, denoted as carry, should be added to high order coefficient.

Since defining carry function is not unique in general, we propose definition of abstract carry system. Let  $\mathbf{c}_{i \rightarrow j} : \mathbb{Z} \rightarrow \mathbb{Z}$  be a carry function for all  $i, j \in \mathbb{N}$  with  $i < j$ . Then we define carry collection  $\mathbf{C}_j$  from  $j = 0$  recursively, and carry system  $\mathbf{C}$  of polynomial ring  $\mathbb{Z}[X]$  as follows:

$$\mathbf{C}_j : \mathbb{Z}[X] \rightarrow \mathbb{Z}, \quad \alpha(X) = \sum_{i=0}^n \alpha_i X^i \mapsto \left[ \alpha_j + \sum_{i=0}^{j-1} (\mathbf{c}_{i \rightarrow j} \circ \mathbf{C}_i)(\alpha(X)) \right], \quad \forall j = 1, 2, \dots$$

$$\mathbf{C} : \mathbb{Z}[X] \rightarrow \mathbb{Z}[X], \quad \alpha(X) = \sum_{j=0}^n \alpha_j X^j \mapsto \sum_{j=0}^n (\pi \circ \mathbf{C}_j)(\alpha(X)) X^j, \quad (14)$$

where  $\mathbf{C}_0(\sum_j \alpha_j X^j) = \alpha_0$ . Intuitively, the carry collection  $\mathbf{C}_j$  adds every carry  $\mathbf{c}_{i \rightarrow j}$  from the coefficient  $i < j$  to the  $j$ -coefficient  $\alpha_j$ . In addition, we call  $\mathbf{C}$  is a *valid* carry system if  $\varphi_\beta(\alpha(X)) = (\varphi_\beta \circ \mathbf{C})(\alpha(X)) \in \mathbb{Q}$  for all  $\alpha(X) \in \mathbb{Z}[X]$ , i.e., sharing the same values when evaluating  $\beta$ . For **ADD**, carry functions  $\mathbf{c}_{i \rightarrow i+1}(x) = (x - \pi(x))/\beta$  are used for all  $i \in \mathbb{N}$ .

The Correctness of **CarryAdd** is as follows: After Algorithm 8 runs every iteration on Line 2, the sign of carry message  $\mathbf{ct}^c$  is the sign of addition of two ciphertexts. However if the sign is negative, yjr packed message polynomial from  $\text{CT}'_0, \dots, \text{CT}'_p$  becomes sign-reversed. To fix its sign, calculated sign in Line 6 is multiplied to  $\text{CT}'$  in Line 7 and bootstrap again.

---

**Algorithm 8**  $(CT'_{\text{frac}}, CT'_{\text{sign}}, (\text{IsZero}_i)_{i \in [p]}) \leftarrow \text{CarryAdd}(CT_{\text{frac}}[m(X)\Delta^2])$

---

1: Set  $\mathbf{ct}^c = 0$  for  $\mathbf{ct}^c \in \mathbb{Z}_Q^{K_{\text{ct}}N_{\text{ct}}+1}$  and  $CT_{\text{frac}} \leftarrow CT_{\text{frac}}X^{-1}$   
2: **for**  $i \in [p+2]$  **do**  
3:    $\text{Tmp}[\Delta^2\mathfrak{C}_i(m(X))] \leftarrow \text{SampleExtract}(CT_{\text{frac}}, i) + \mathbf{ct}^c$   
4:    $\mathbf{ct}''_i[\Delta(\pi \circ \mathfrak{C}_i)(m(X))], \mathbf{ct}^c[\Delta^2(\mathfrak{c}_{i \rightarrow i+1} \circ \mathfrak{C}_i)(m(X))] \leftarrow \text{Bootstraps Tmp}$   
5: **end for**  
6:  $CT'_{\text{sign}} \leftarrow$  sequential bootstrap with  $CT^c$  and extract its sign.  
7:  $CT' \leftarrow \text{Packing}$  with  $\mathbf{ct}'_0, \dots, \mathbf{ct}'_p$  and  $\text{TensorProd}$  with  $CT'_{\text{sign}}$   
8: **for**  $i \in [p+2]$  **do**  
9:    $(\mathbf{ct}''_i, \mathbf{ct}^c, \text{IsZero}_i) \leftarrow \text{Bootstrap SampleExtract}(CT', i) + \mathbf{ct}^c \triangleright$  where  $\text{IsZero}_i$  has a message  $m\Delta$  with  $m = 1$  if message of  $CT''_i$  is zero, and  $m = 0$  otherwise  
10: **end for**  
11: **return**  $(CT'_{\text{frac}} \leftarrow \text{Packing}((\mathbf{ct}''_i)_{i \in [p+2]}), CT'_{\text{sign}}, (\text{IsZero}_i)_{i \in [p+1]})$

---

In addition, **ADD** checks whether each coefficient of  $\mathfrak{C}(m(X))$  is zero or not and generates a ciphertext  $\text{IsZero}_i$  containing boolean message above information. This ciphertext is used to calculate *normal form*.

**ACCPoly 6-8.** Used for generating carry and IsZero ciphertexts in Algorithm 8

output \ location (adding $8\Delta^2$ )	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1st outputs ( $\times \Delta$ )	0	1	2	3	0	1	2	3	0	1	2	3	0	1	2	3
2nd outputs ( $\times \Delta^2$ )	-2	-2	-2	-2	-1	-1	-1	-1	0	0	0	0	1	1	1	1

output \ location (adding $8\Delta^2$ )	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
1st outputs ( $\times \Delta$ )	0	1	2	3	0	1	2	3	0	1	2	3	0	1	2	3
2nd outputs ( $\times \Delta$ )	-1	-1	-1	-1	-1	-1	-1	-1	1	1	1	1	1	1	1	1

output \ location (adding $4\Delta^2$ )	0	1	2	3	4	5	6	7
1st outputs ( $\times \Delta$ )	0	1	2	3	0	1	2	3
2nd outputs ( $\times \Delta^2$ )		-1	-1	-1	-1	0	0	0
3st outputs ( $\times \Delta$ )		1	0	0	0	1	0	0

To implement and accelerate **CarryAdd** in our (4,27,-511,511) floating-point FHE, **ACCPoly 6** is used for bootstrapping in Line 4. Note that the  $i$ -th coefficient message  $m_i$  of corresponding to the sum of two fraction polynomials takes a value between from  $-6$  and  $6$ . If a carry message takes a value from  $-2$  to  $1$ , then  $CT'_i$  and  $CT^c$  can be obtained by adding  $8\Delta^2$  and bootstrapping with **ACCPoly 6**. When bootstrapping with index  $i = p + 1$  on Line 3, **ACCPoly 7** is used to obtaining the sign of fraction message. Note that a  $i$ -th coefficient message  $m_i$  after packing and doing tensor product in Line 8 is the value between  $-3$  and  $3$ . Therefore, we obtain  $CT''_i$ ,  $CT^c$ , and  $\text{IsZero}_i$  by adding  $4\Delta^2$  and then bootstrapping using **ACCPoly 8**.

Similar to **CarryAdd**, homomorphic carry over for multiplication is proposed Algorithm 9, denoted as **CarryMul** with *valid*  $\mathfrak{C}$  with carry functions  $\mathfrak{c}_{i \rightarrow j}$ .

---

**Algorithm 9** ( $\text{CT}'_{\text{frac}}, (\text{IsZero}_i)_{i \in [p]} \leftarrow \text{CarryMul}(\text{CT}_{\text{frac}}[m(X)\Delta^2])$ )

---

- 1:  $\text{ct}_i^c = 0$ , where  $\text{ct}_i^c \in \mathbb{Z}_Q^{K_{\text{ct}} N_{\text{ct}} + 1}$ , for all  $i \in [2p]$
- 2: **for**  $i \in [2p]$  **do**
- 3:    $(\text{ct}'_i[\Delta(\pi \circ \mathfrak{C}_i)(m(X))], (\text{ct}_j^{cc}[\Delta^2(\mathfrak{c}_{i \rightarrow j} \circ \mathfrak{C}_i)(m(X))]])_j, \text{IsZero}_i \leftarrow$  Sequential bootstrap with **SampleExtract**( $\text{CT}_{\text{frac}}, i$ ) +  $\text{ct}_i^c$
- 4:   Update carry  $\text{ct}_j^c += \text{ct}_j^{cc}$  for all  $j > i$  of generated carry ciphertexts
- 5: **end for**
- 6: **return** ( **Packing**( $\text{ct}'_i)_{i \in [2p]}, (\text{IsZero}_i)_{i \in [2p]}$ )

---

To implement and accelerate **CarryMul** in our (4,27,-511,511) floating-point FHE, carry functions are designed as follows: for any given  $i$ -th coefficient of  $l$ -bit message  $m = (m_{l-1} \dots m_0)_{(2)}$ , set  $\mathfrak{c}_{i \rightarrow i+1}(m\Delta^2) = (m_3 m_2)_{(2)}$  and  $\mathfrak{c}_{i \rightarrow i+2j}(m) = (m_{4j+3} m_{4j+2} m_{4j+1} m_{4j})_{(2)}$  for all  $j \geq 1$ . Then carry functions are constructed efficiently by using **ACCPoly 9** as follows: If  $l \leq 4$ , then ciphertexts of messages and carry are obtained by using sequential bootstrapping ones. Otherwise, **ACCPoly 9** is used and obtains four ciphertexts having messages  $(-1)^{m_3}(m_1 m_0)_{(2)}\Delta$ ,  $(-1)^{m_3}(m_2)_{(2)}\Delta$ ,  $(-1)^{m_3}\Delta$ , and  $(-1)^{m_3}\Delta^2$ . Then sign of two for first and second ciphertexts can be removed by doing tensor product with third ciphertext. Finally, we obtain a ciphertext with message  $2m_3\Delta^2$  by using forth ciphertext and adding  $\Delta^2$ .

**ACCPoly 9.** Used for generating carry in Algorithm 9

output \ location	0	1	2	3	4	5	6	7
1st outputs ( $\times \Delta$ )	0	1	2	3	0	1	2	3
2nd outputs ( $\times \Delta$ )	0	0	0	0	1	1	1	1
3rd outputs ( $\times \Delta$ )	1	1	1	1	1	1	1	1
4th outputs ( $\times \Delta^2$ )	1	1	1	1	1	1	1	1

For accelerating **CarryMul**, upper-bound of  $\mathfrak{C}_i(m_1(X)m_2(X))$  can be analyzed for any *valid* fraction message polynomials  $m_1(X)$  and  $m_2(X)$  by following Proposition 4.

**Proposition 4.** *Suppose that two polynomials  $a(X), b(X) \in \mathbb{N}[X]$  are given with each coefficient satisfy  $a_i \leq b_i$  and carry functions  $\mathfrak{c}_{i \rightarrow j} : \mathbb{N} \rightarrow \mathbb{N}$  are given for all  $i, j \in \mathbb{N}$  satisfying  $\mathfrak{c}_{i \rightarrow j}(x) \leq \mathfrak{c}_{i \rightarrow j}(y)$  if  $x \leq y$  for all  $x, y \in \mathbb{N}$ . Then following inequality  $\mathfrak{C}_j(a(X)\alpha(X)) \leq \mathfrak{C}_j(b(X)\alpha(X))$  holds for all  $j$ -coefficient and  $\alpha(X) \in \mathbb{N}[X]$ .*

*Proof.* Since every coefficient of  $b(X)$  is greater than or equal  $a(X)$ , following equation  $\mathfrak{C}_0(a(X)\alpha(X)) = a_0\alpha_0 \leq b_0\alpha_0 \leq \mathfrak{C}_0(b(X)\alpha(X))$  holds. To induct on  $j$ , let assume  $\mathfrak{C}_0, \dots, \mathfrak{C}_{j-1}$  satisfies Proposition 4. Then for every index  $j \in \mathbb{N}$ ,

$$\begin{aligned} \mathfrak{C}_j(a(X)\alpha(X)) &= \sum_{i \in [j+1]} a_i \alpha_{j-i} + \sum_{i \in [j]} (\mathfrak{c}_{i \rightarrow j} \circ \mathfrak{C}_i)(a(X)\alpha(X)) \\ &\leq \sum_{i \in [j+1]} b_i \alpha_{j-i} + \sum_{i \in [j]} (\mathfrak{c}_{i \rightarrow j} \circ \mathfrak{C}_i)(b(X)\alpha(X)) = \mathfrak{C}_j(b(X)\alpha(X)) \end{aligned}$$

□

Therefore,  $\mathfrak{C}_i(m_1(X)m_2(X)) \leq \mathfrak{C}_i(m_1(X)m_{\max}(X)) \leq \mathfrak{C}_i(m_{\max}^2(X))$  is upper bound for any product of two message polynomial by using Proposition 4 with polynomial  $m_{\max}(X) = (\beta - 1)\Delta \sum_{j=0}^{p-1} X^j$ .

From Proposition 4, we obtain condition for  $Q_0$  such that  $2^{\eta_0 - \eta_1} > \log \max_i \mathfrak{C}_i(m_{\max}^2(X))$ . Otherwise, messages are deformed due to small  $Q_0$ . Moreover,  $\max_i \mathfrak{C}_i(m_{\max}^2(X))$  can be pre-calculated and it is upper-bounded by  $2^{10}$  for our carry system and selected parameters. Therefore, index  $i$  is enough to assign from  $p - 3$  to  $2p - 1$  in Line 2 since every index  $i \leq p - 4$  cannot influence index  $p$ .

### 5.3 Algorithm for normalizing after homomorphic floating-point operations

When **CarryAdd** or **CarryMul** are ended, fraction and exponent should be adjusted to a *normal form*. The first step is counting the number of zeros from most significant in fraction and stopping when nonzero values are occurred. We propose **HomeCount** as Algorithm 10 as follows:

---

**Algorithm 10** :  $\text{Out} \leftarrow \mathbf{HomCount}((\text{IsZero})_{i \in [p']})$

---

- 1:  $\text{CT}_1[\Delta m_{p'-1}] \leftarrow \text{IsZero}_{p'-1}[\Delta m_{p'-1}]$
  - 2:  $\text{Out}[\Delta^2 m_{p'-1}] \leftarrow \Delta \text{IsZero}_{p'-1}[\Delta m_{p'-1}]$
  - 3: **for**  $i \in [p' - 1]$  **do**
  - 4:      $(\text{CT}_1[\Delta \prod_{j=i}^{p'-1} m_j], \text{CT}_2[\Delta^2 \prod_{j=i}^{p'-1} m_j]) \leftarrow \text{Sequential bootstrap and Packing with TensorProd}(\text{CT}_1, \text{IsZero}_i)$
  - 5:      $\text{Out} += \text{CT}_2$
  - 6: **end for**
  - 7: **return**  $\text{Out}[m\Delta'] \leftarrow \text{Bootstrap Out}$ , where  $m$  is a number of zeros until nonzero significant occurs
- 

When **HomCount** runs on the Line 4, product of  $\text{CT}_1$  and  $\text{IsZero}_i$  acts like AND gate. Therefore, every returned ciphertexts  $\text{CT}_1$  in Line 4 encrypt  $\Delta$  until  $\text{IsZero}_i$  encrypts 0 for the first index  $i$ , and encrypt 0 after  $i$ -iteration. Then, **HomCount** adds all returned ciphertext  $\text{CT}_2$  to  $\text{Out}$  in Line 5, which has

message scaled by  $\Delta^2$ . Finally, we bootstrap Out and obtains ciphertext with message having a number of zeros until nonzero significant occurs.

By using Algorithm **HomCount**, we proposes Algorithm 11, denoted as **Normalize** to normalize fraction and exponent on the ciphertext. Since the number of nonzero significant fraction are calculated by using **HomCount**, **Normalize** can subtracts it from exponent ciphertext. However subtracted messages can be less than  $e_{\min}$ , therefore **Normalize** evaluates **Min** and subtracts its output from exponent ciphertext. In addition, the min ciphertext having constant message converts to the MulCT having message in monomial exponent by using **ConstToExp** in Line 2. Then fraction can be adjusted to *normal form* by doing tensor product with MulCT and  $CT_{\text{frac}}$ .

---

**Algorithm 11**  $Out_{\text{frac}}, Out_{\text{exp}} \leftarrow \mathbf{Normalize}((\text{IsZero}_i)_{i \in [p]}, CT_{\text{exp}}, CT_{\text{frac}})$

---

- 1:  $CT_{\text{exp}}^{\min} = \mathbf{Min}(\mathbf{HomCounter}((\text{IsZero}_i)_{i \in [p]}), CT_{\text{exp}})$
  - 2:  $CT_{\text{tmp}} = \mathbf{ConstToExp}(CT_{\text{exp}}^{\min})$
  - 3:  $Out_{\text{frac}} \leftarrow \mathbf{SampleExtract}(\cdot, i)$ , Bootstrap and **Packing** from **Tensor-Prod**( $CT_{\text{tmp}}, CT_{\text{frac}}$ ) for all  $i \in [p]$
  - 4: **return** ( $Out_{\text{frac}}, CT_{\text{exp}} - CT_{\text{exp}}^{\min}$ )
- 

#### 5.4 Generating a proof to detect overflow occurrence

In this section, we propose an algorithm to generate ciphertext having message of overflow occurrence. Since message space  $\mathcal{M} \subseteq \mathbb{R}$  for encrypting real numbers is finite in practice, unique maximum and minimum norm values  $|x|$  for  $x \in \mathcal{M} \setminus \{0\}$  exist. Let  $U_{\mathcal{M}}$  and  $L_{\mathcal{M}}$  be the maximum and minimum norm values, respectively. Assume that finite  $n$  messages  $x_i \in \mathcal{M}$  for  $i \in [n]$  and bounded depth arithmetic circuit  $f : \mathcal{M}^n \rightarrow \mathbb{R}$  are given.  $\mathbf{x}$  are called  $f$ -overflow numbers if  $|f(\mathbf{x})| > U_{\mathcal{M}}$  and if a norm value of any intermediate result is greater than  $U_{\mathcal{M}}$  while evaluating  $f$ , it is called that an overflow occurs.

It is clear that CKKS has  $f$ -overflow numbers for any circuit  $f$  due to the finite message space in  $\mathbb{C}$ . Note that original BGV/FV do not show  $f$ -overflow numbers because it uses a message space with  $t$ -characteristic ring for some  $t \in \mathbb{N}$ . However, if BGV/FV are used to encrypt a subset of  $\mathbb{Z}$ , then  $f$ -overflow numbers exist.

Since the messages of calculated ciphertext cannot be checked during homomorphic operations, overflow occurrence has to be informed to a user by generating extra ciphertext having such information as a message. Generation of those for CKKS and BGV/FV is a complicated problem because fixed-point operations are used and it may require a lot of extra precision to save and check overflowed-results. In FPFHE, however, inspection of the exponent is enough to check overflow and just extra one bit precision in exponent is required. We propose Algorithm 12, denoted as **GenProof** is proposed, which

uses  $e' = \lfloor \log \max(|e_{\max} - 1|, |e_{\max} - 2e_{\min} + 1|) \rfloor + 1$  to generate MLWE ciphertext for the message indicating whether the message of  $\text{CT}_{\text{exp}}$  is larger than  $e_{\max}$  or not and this ciphertext is called a proof.

---

**Algorithm 12**  $\text{proof}' \leftarrow \text{GenProof}(\text{CT}_{\text{exp}}, \text{proof})$

---

**Input**  $\text{CT}_{\text{exp}}[m\Delta']$ ,  $\text{proof}[m_{pf}\Delta']$

**Output**  $\text{proof}'[(m_{pf} + \alpha)\Delta']$  with  $\alpha = 1$  if  $m > e_{\max}$ , and  $\alpha = 0$  otherwise

- 1:  $\text{CT}[(m_{e'-1} \dots m_0)_{(2)}\Delta'] = \text{CT}_{\text{exp}} + (2^{e'} - e_{\max} - 1)\Delta'$
  - 2:  $\text{proof}'[\alpha\Delta'] \leftarrow$  Use sequential bootstrap to have a message  $\alpha = 1 - m_{e'-1}$
  - 3: **return**  $\text{proof}' \leftarrow \text{proof} + \text{proof}'$
- 

**GenProof** is analogous to the **Max** which operates as follows: If the previous proof has a message 0, i.e., an overflow does not occur while performing the previous operations, then the message  $m$  is in  $2e_{\min} \leq m \leq 2e_{\max}$ . Therefore,  $m' = e_{\max} - m + 1$  is strict positive if and only if  $m \leq e_{\max}$ . Moreover,  $e'$ -bit from binary representation of  $2^{e'} - m'$  is one if and only if  $m'$  is strict positive, meaning that  $\text{proof}'$  in Line 2 has a message of whether  $m > e_{\max}$  or not.

Otherwise if the previous proof has a non-zero message, then it already contains the information of overflow occurrence. Then, by returning the proof that is the sum of all previous proofs, a user can check whether an overflow occurs or not by decrypting the proof. Therefore, by using the proposed OD-FPFHE and given bootstrapping failure probability  $2^{-\Omega(v)}$ , a user can detect  $f$ -overflow numbers for any  $\text{poly}(v)$  bounded function  $f$ .

## 6 Security analysis

This paper relies on key-dependent message(KDM) and circular security assumption to generate public keys [8, 17, 19] which is used for FHEs. To determine concrete parameter values of OD-FPFHE for achieving target security, we estimate the computational complexity of Primal uSVP and dual lattice attack using  $k$ -block BKZ with SVP oracle having the sieving cost  $2^{0.292k+16.4}$  [3]. In addition, we apply hybrid primal and dual attack [12] to LWE key-switching key encrypted by  $h$ -sparse **sk-ks**. Such derived concrete parameters are listed in Table 1.

In Table 1 the number after D and S refers to the security level. For instance, parameters D128 guarantees 128-bit security for Primal, Dual, and hybrid attacks. D and S refer to the double and signal precision of OD-FPFHE, respectively. Note that, OD-FPFHE with D128 can deal with the ciphertexts for double and single precision messages, but however OD-FPFHE with S128 can deal with the ciphertexts for single precision messages only.

**Table 1:** Concrete parameters of OD-FPFHE for various security levels

\	$n$	$K_{ct}$	$N_{gct}$	$K_{gct}$	$n$	$Q_0 - 1$	$Q_1 - 1$	$q$	$B_{bl}$	$B_{pack}$	$B_{ev}$	$B_{ks}$	$h$
D128	$2^8$	13	$2^{11}$	2	785	$521 \cdot 2^{39}$	$521 \cdot 2^{29}$	$2^{21}$	$2^{12}$	$2^{16}$	$2^{18}$	2	131
D160	$2^8$	16	$2^{11}$	2	1089	$521 \cdot 2^{39}$	$521 \cdot 2^{29}$	$2^{21}$	$2^{10}$	$2^{14}$	$2^{18}$	2	131
D192	$2^8$	19	$2^{11}$	3	1292	$521 \cdot 2^{39}$	$521 \cdot 2^{29}$	$2^{22}$	$2^{10}$	$2^{13}$	$2^{18}$	2	160
S128	$2^8$	13	$2^{12}$	1	785	$135 \cdot 2^{36}$	$135 \cdot 2^{30}$	$2^{21}$	$2^{12}$	$2^{16}$	$2^{18}$	2	131
S160	$2^8$	15	$2^{12}$	1	1089	$135 \cdot 2^{36}$	$135 \cdot 2^{30}$	$2^{21}$	$2^{12}$	$2^{16}$	$2^{18}$	2	131
S192	$2^8$	18	$2^{11}$	3	1292	$135 \cdot 2^{36}$	$135 \cdot 2^{30}$	$2^{22}$	$2^{10}$	$2^{14}$	$2^{18}$	2	160

## 7 Simulation results and conclusions

We implement (4,27,-511,511) and (4,12,-127,127) floating-point number system by using PALISADE v1.11. Simulation is performed by running Ubuntu 20.04 LTS over Intel(R) Xeon(R) Silver 4210R CPU @ 2.40GHz having 20 core 40 threads and 256 GB of RAM. PALISADE is compiled with the following CMake flags: WITH-NATIVEOPT=ON (machine-specific optimizations were applied by the compiler) and WITH-INTEL-HEXL= ON (AVX-512 acceleration was used), by Clang++10.0.0. Running times for various parameters are listed in Table 2. Since S128, S160, and S190 does not support double precision, the time consumption is not available for these cases.

We simulate Algorithms 4 and 5 by using the number of 1 (single-core), 4, and 10 threads using parameters in Table 1, and list the operation time in Table 2. In addition, we simulate addition and multiplication time per threads, which is listed in Table 2 as Amortized time. Therefore, if many thread are available, run time is expected to approach to the amortized time if a circuit is evaluated parallel such as matrix multiplication. However if a circuit is evaluated by sequential operations, run time is expected to approach to the Time (10 thread) in Table 2.

Next, we arbitrary choose double and single precision messages  $x$  without encoding error i.e.,  $\mathbf{Decode}(\mathbf{Encode}(x)) = x$  as follows:

$$\begin{aligned}
 x_d^1 &= -9.1763514236254290 * 10^{-32}, & x_d^2 &= 6.2467247246375865 * 10^{-24}, \\
 x_d^3 &= 2.4523526872362373 * 10^{22}, & x_d^4 &= -5.4324663335297274 * 10^{17}, \\
 x_f^1 &= -2.7914999921796382 * 10^{-15}, & x_f^2 &= 8.3867001884896375 * 10^{-12}, \\
 x_f^3 &= 1.82634005135360 * 10^{14}, & x_f^4 &= -6.278269952 * 10^9,
 \end{aligned}$$

where  $x_d^i$  and  $x_f^i$  denote double and single precision message, respectively. Then we evaluate  $z_1 = (x_1 + x_2)$ ,  $z_2 = (x_3 - x_4)$ ,  $z_3 = z_1 \cdot z_2$ , and  $z_4 = z_3^2$  on the ciphertext domain, and results are listed in Table 3 and 4 and correct calculation values are listed which is round down. It can be directly checked that error between correct values and decryption result where overflow is not occur is bounded as known as Proposition 3.

Also, we perform the previous circuits with single precision floating-point numbers  $x_f^1$ ,  $x_f^2$ ,  $x_f^3$ , and  $x_f^4$  and results are as given in Table 4.

**Table 2:** Time consumption for various parameters (second)

Addition		<b>D128</b>	D160	D192	<b>S128</b>	S160	S192
Single precision	Time (1 thread)	<b>530</b>	823	1516	<b>525</b>	700	1495
	Time (4 thread)	<b>264</b>	374	657	<b>239</b>	321	654
	Time (10 thread)	<b>181</b>	269	452	<b>183</b>	248	423
	Amortized time	<b>57.5</b>	70.2	131	52.1	66.8	130
Double precision	Time (1 thread)	<b>858</b>	1303	2439	-	-	-
	Time (4 thread)	<b>366</b>	543	950	-	-	-
	Time (10 thread)	<b>256</b>	387	630	-	-	-
	Amortized time	<b>103</b>	112	253	-	-	-
Multiplication		<b>D128</b>	D160	D192	<b>S128</b>	S160	S192
Single precision	Time (1 thread)	<b>443</b>	674	1257	<b>426</b>	580	1236
	Time (4 thread)	<b>223</b>	314	551	<b>203</b>	282	530
	Time (10 thread)	<b>169</b>	249	392	<b>168</b>	226	383
	Amortized time	<b>42.7</b>	61.1	112	49.7	61.2	112
Double precision	Time (1 thread)	<b>808</b>	1230	2303	-	-	-
	Time (4 thread)	<b>402</b>	565	946	-	-	-
	Time (10 thread)	<b>293</b>	438	704	-	-	-
	Amortized time	<b>110</b>	165	190	-	-	-

**Table 3:** double precision(64-bit) operation results

\	$x_d^1 + x_d^2$	$x_d^3 - x_d^4$
Correct value	<b>6.2467246328740732</b> · 10 <sup>-24</sup>	<b>2.45240701189957269</b> · 10 <sup>22</sup>
OD-FPFHE	<b>6.2467246328740717</b> · 10 <sup>-24</sup>	<b>2.45240701189957230</b> · 10 <sup>22</sup>
\	$(x_d^1 + x_d^2)(x_d^3 - x_d^4)$	$[(x_d^1 + x_d^2)(x_d^3 - x_d^4)]^2$
Correct value	<b>0.153195112910661</b>	<b>0.023468742619710</b>
OD-FPFHE	<b>0.153195112910657</b>	<b>0.023468742619709</b>

**Table 4:** single precision(32-bit) operation results

\	$x_f^1 + x_f^2$	$x_f^3 - x_f^4$
Correct value	<b>8.38390868</b> · 10 <sup>-12</sup>	<b>1.82640283</b> · 10 <sup>14</sup>
OD-FPFHE	<b>8.38390815</b> · 10 <sup>-12</sup>	<b>1.82640279</b> · 10 <sup>14</sup>
\	$(x_f^1 + x_f^2)(x_f^3 - x_f^4)$	$[(x_f^1 + x_f^2)(x_f^3 - x_f^4)]^2$
Correct value	<b>1531.23945</b>	<b>2344694.28</b>
OD-FPFHE	<b>1531.23937</b>	<b>2344694.00</b>

Since the precision  $p = 12$  for single precision is less than  $p = 27$  for double precision, the error values between correct and decryption result in Table 4 is bigger than Table 3. However, errors are bounded properly bounded as known as 3 when overflow is not occurs.

In addition, we choose following numbers DBL-MAX, DBL-MIN, FLT-MAX and FLT-MIN which are maximum and minimum of double and single preci-

sion floating-point numbers, respectively, where these are provided in standard library in C++ language. We evaluate DBL-MAX·1000, DBL-MIN·0.001, FLT-MAX·1000, and FLT-MIN·0.001 on the ciphertext. All of decrypted results are invalid however, message of Proof ciphertext was not a zero, meaning that overflow is occurs. These all simulation codes are opened in public.

**Conclusions and future works** In this paper, We proposed a floating-point fully homomorphic encryption. Since floating-point number system is widely used in many areas such as deep learning models, the proposed FPFHE can guarantee both privacy and accuracy for many applications. In addition, we proposed an OD-FPFHE, which has many applications. For instance, it is quite useful for continual learning models while keeping the privacy of training data such as privacy-preserving federated learning because the encrypted training data can be excluded from the training to avoid learning degeneration when it results in overflow.

**future works and open problems** Since many applications need accurate floating-point division algorithm, more accurate and efficient division algorithm should be constructed. In addition, efficient floating-point homomorphic elementary functions such as exponential, logarithm, and  $N$ -th root function are also desirable in privacy-preserving machine learning.

The critical disadvantage of OD-FPFHE is having slower operation time. However, speed of operation can be improved in further researches as follows: Since large modulus  $Q$  affects bootstrapping time slower, a method of reducing a size of  $Q$  should be investigated. For instance, randomized gadget decomposition are reported that it reduces error amplification after running GSW-like multiplication[16]. Therefore, effective randomized gadget decomposition for OD-FPFHE and both rigorous and practical error analysis will improve speed of operation time.

**Acknowledgements** This work was supported by the Samsung Research Funding and Incubation Center of Samsung Electronics under Project SRFC-IT1801-08

## References

1. Agrawal, S., Goldwasser, S., Mossel, S.: Deniable fully homomorphic encryption from learning with errors. In: Annual International Cryptology Conference. pp. 641–670. Springer (2021)
2. Albrecht, M., Chase, M., Chen, H., Ding, J., Goldwasser, S., Gorbunov, S., Halevi, S., Hoffstein, J., Laine, K., Lauter, K., et al.: Homomorphic encryption standard. In: Protecting Privacy through Homomorphic Encryption, pp. 31–62. Springer (2021)
3. Albrecht, M.R., Player, R., Scott, S.: On the concrete hardness of learning with errors. *Journal of Mathematical Cryptology* **9**(3), 169–203 (2015)

4. Badrinarayanan, S., Miao, P., Raghuraman, S., Rindal, P.: Multi-party threshold private set intersection with sublinear communication. In: IACR International Conference on Public-Key Cryptography. pp. 349–379. Springer (2021)
5. Beaulieu-Jones, B.K., Wu, Z.S., Williams, C., Lee, R., Bhavnani, S.P., Byrd, J.B., Greene, C.S.: Privacy-preserving generative deep neural networks support clinical data sharing. *Circulation: Cardiovascular Quality and Outcomes* **12**(7), e005122 (2019)
6. Bourse, F., Minelli, M., Minihold, M., Paillier, P.: Fast homomorphic evaluation of deep discretized neural networks. In: Annual International Cryptology Conference. pp. 483–512. Springer (2018)
7. Brakerski, Z., Gentry, C., Vaikuntanathan, V.: (leveled) fully homomorphic encryption without bootstrapping. *ACM Transactions on Computation Theory (TOCT)* **6**(3), 1–36 (2014)
8. Brakerski, Z., Vaikuntanathan, V.: Fully homomorphic encryption from ring-lwe and security for key dependent messages. In: Annual cryptology conference. pp. 505–524. Springer (2011)
9. Capiński, M., Kopp, P.E.: *Measure, integral and probability*, vol. 14. Springer (2004)
10. Case, B.M., Gao, S., Hu, G., Xu, Q.: Fully homomorphic encryption with k-bit arithmetic operations. *Cryptology ePrint Archive* (2019)
11. Cheon, J.H., Han, K., Kim, A., Kim, M., Song, Y.: Bootstrapping for approximate homomorphic encryption. In: Annual International Conference on the Theory and Applications of Cryptographic Techniques. pp. 360–384. Springer (2018)
12. Cheon, J.H., Hhan, M., Hong, S., Son, Y.: A hybrid of dual and meet-in-the-middle attack on sparse and ternary secret lwe. *IEEE Access* **7**, 89497–89506 (2019)
13. Chillotti, I., Gama, N., Georgieva, M., Izabachène, M.: Tfhe: fast fully homomorphic encryption over the torus. *Journal of Cryptology* **33**(1), 34–91 (2020)
14. Chillotti, I., Joye, M., Paillier, P.: Programmable bootstrapping enables efficient homomorphic inference of deep neural networks. In: International Symposium on Cyber Security Cryptography and Machine Learning. pp. 1–19. Springer (2021)
15. Chillotti, I., Ligier, D., Orfila, J.B., Tap, S.: Improved programmable bootstrapping with larger precision and efficient arithmetic circuits for tfhe. In: International Conference on the Theory and Application of Cryptology and Information Security. pp. 670–699. Springer (2021)
16. Genise, N., Micciancio, D., Polyakov, Y.: Building an efficient lattice gadget toolkit: Subgaussian sampling and more. In: Annual International Conference on the Theory and Applications of Cryptographic Techniques. pp. 655–684. Springer (2019)
17. Gentry, C.: Fully homomorphic encryption using ideal lattices. In: Proceedings of the forty-first Annual ACM Symposium on Theory of Computing. pp. 169–178 (2009)
18. Gentry, C., Halevi, S.: Compressible fhe with applications to pir. In: Theory of Cryptography Conference. pp. 438–464. Springer (2019)
19. Gentry, C., Sahai, A., Waters, B.: Homomorphic encryption from learning with errors: Conceptually-simpler, asymptotically-faster, attribute-based. In: Annual Cryptology Conference. pp. 75–92. Springer (2013)
20. Jäschke, A., Armknecht, F.: Accelerating homomorphic computations on rational numbers. In: International Conference on Applied Cryptography and Network Security. pp. 405–423. Springer (2016)
21. Kairouz, P., McMahan, H.B., Avent, B., Bellet, A., Bennis, M., Bhagoji, A.N., Bonawitz, K., Charles, Z., Cormode, G., Cummings, R., et al.: Advances and open problems in federated learning. *arXiv preprint arXiv:1912.04977* (2019)

22. Lee, J.W., Lee, E., Lee, Y., Kim, Y.S., No, J.S.: High-precision bootstrapping of rns-ckks homomorphic encryption using optimal minimax polynomial approximation and inverse sine function. In: Annual International Conference on the Theory and Applications of Cryptographic Techniques. pp. 618–647. Springer (2021)
23. Micciancio, D., Polyakov, Y.: Bootstrapping in fhe-like cryptosystems. In: Proceedings of the 9th Workshop on Encrypted Computing & Applied Homomorphic Cryptography. pp. 17–28 (2021)
24. Moon, S., Lee, Y.: An efficient encrypted floating-point representation using heaan and tthe. *Security and Communication Networks* (2020)
25. Mukherjee, T., Stephens-Davidowitz, N.: Lattice reduction for modules, or how to reduce modulesvp to modulesvp. In: Annual International Cryptology Conference. pp. 213–242. Springer (2020)
26. Muller, J.M., Brisebarre, N., De Dinechin, F., Jeannerod, C.P., Lefevre, V., Melquiond, G., Revol, N., Stehlé, D., Torres, S., et al.: *Handbook of floating-point arithmetic*, vol. 1. Springer (2018)
27. Neukirch, J.: *Algebraic number theory*, vol. 322. Springer Science & Business Media (2013)
28. Rajaraman, V.: Ieee standard for floating point numbers. *Resonance* **21**(1), 11–30 (2016)
29. Regev, O.: On lattices, learning with errors, random linear codes, and cryptography. *Journal of the ACM (JACM)* **56**(6), 1–40 (2009)
30. Rigollet, P., Hütter, J.C.: High dimensional statistics. Lecture notes for course 18S997, **813**(814), 46 (2015)

## Supplementary material

Omitted algorithms and proofs in the main paper are listed.

### Proof of Lemma 4

*Proof.* When Algorithm 2 runs every  $i$  on line 2, added error can be expressed as

$$\begin{aligned} & \sum_{j \in [l_{\text{bl}}]} (X^{a_i} - 1) G_{\text{crt}}^{-1}(\text{ACC}^{(i)}) E_j^1(X) + \sum_{j \in [l_{\text{bl}}]} (X^{-a_i} - 1) G_{\text{crt}}^{-1}(\text{ACC}^{(i)}) E_j^{-1}(X) \\ & + \sum_{j \in [l_{\text{bl}}]} [(X^{a_i} - 1) A_j^1(X) + (X^{-a_i} - 1) A_j^{-1}(X)] \text{sk-bl}(X)_j, \end{aligned} \quad (15)$$

by using (3) and previous CMux gate analysis (See Section 3.4 of [13]) where  $\text{ACC}^{(i)}$  is the computed value after  $i - 1$  th iteration on line 3,  $A_j^1$  and  $A_j^{-1}$  are a gadget error polynomial,  $E_j^1(X)$  and  $E_j^{-1}(X)$  are the  $j$ -column error polynomial of  $\text{BL}_i^1$  and  $\text{BL}_i^{-1}$ , respectively.

Since errors and secret key having symmetric distribution and independent of the multiplied bounded random variable respectively, these random variables have *Pythagorean additivity* by using Corollary 2. After iteration of  $i$ , first and second summation errors in (15). After inducting on  $i$  and by using *negacyclic property*, and Proposition 1, we obtain (10).  $\square$

### Algorithm Packing and proof of Lemma 5

---

**Algorithm 13** :  $\text{OUT} \leftarrow \mathbf{Packing}((\text{ct}_i)_{i \in [p]}, ev)$

---

**Input:**  $(\text{ct}_i[\Delta m_i])_{i \in [p]} \in \prod_{i \in [p]} \mathbb{Z}_Q^{N_{\text{gct}} K_{\text{gct}} + 1}$ ,

**Output:**  $\text{OUT}[\Delta \sum_{i \in [p]} m_i X^i] \in R_{N_{\text{ct}}, Q}^{K_{\text{ct}} + 1}$

- 1: Set  $\text{OUT} = (0(X), \dots, \sum_{i \in [p]} b_i X^i)$   $\triangleright$  where  $b_i$  is the  $b$  of  $\text{ct}_i$
  - 2: **for**  $(i, j, x) \in [p, K_{\text{gct}}, N_{\text{gct}}]$  **do**
  - 3:      $v = G_{\text{crt}}^{-1}(\text{CT}_{i,j,x})$
  - 4:      $\text{OUT} += \sum_{y \in [l_{\text{pack}}]} v_y P_{j,x,y} X^i$
  - 5: **end for**
  - 6: **return**  $\text{OUT}$
- 

*Proof.* Let  $\text{OUT}$  be a  $(0(X), \dots, \sum_i b^{(i)}(X))$  as written line 1 in **Packing**. Then, the decryption result of returning Algorithm 13 as follows:

$$\varphi \left( \text{OUT} + \sum_{i,j,x,y} G_{\text{crt}}^{-1}(\text{CT}_{i,j,x})_y P_{j,x,y} X^i \right)$$

$$\begin{aligned}
&= \sum_i b^{(i)}(X) + \sum_{i,j,x,y} G_{\text{crt}}^{-1}(\text{CT}_{i,j,x,y})(sk-bl_{j,x}B_{\text{pack}}^{y+1} + E'_{j,x,y}(X))X^i \\
&= \sum_i \varphi(\text{CT}_i)X^i + \sum_{j,x} \left( \sum_i A'_{j,x,y}X^i \right) sk-bl_{j,x} + \sum_{i,j,x,y} G_{\text{crt}}^{-1}(\text{CT}_{i,j,x,y})X^i E'_{j,x,y}(X),
\end{aligned} \tag{16}$$

where  $A'_{j,x,y}$  is a gadget error, and  $E'_{j,x,y}(X)$  is the error polynomial of packing key  $P_{j,x,y}$ . Since errors  $E'_{j,x,y}(X)$  and secret key  $sk-bl_{j,x}$  have symmetric distribution and are independent of the multiplied bounded random variable respectively, the second and third summations in (16) have *Pythagorean additivity* by using Corollary 2. Since the first summation in (16) is  $\sum_i (\Delta m_i X^i + \mathcal{E}_{\text{bl}}^{(i)})$ , hence (11) holds.  $\square$

### Algorithm of TensorProd and proof of Lemma 6

---

**Algorithm 14** :  $\text{OUT} \leftarrow \text{TensorProd}(\text{CT}_1, \text{CT}_2, ev)$

---

**Input**  $\text{CT}_1[\Delta m(X)] = (a_0, \dots, a_{K_{\text{ct}}-1}, b)$ ,  $\text{CT}_2[\Delta m(X)] = (\mathbf{a}_0, \dots, \mathbf{a}_{K_{\text{ct}}-1}, \mathbf{b}) \in R_{n,Q}^{K_{\text{ct}}+1}$

**Output**  $\text{OUT}[\Delta^2 m(X)m(X)] \in R_{n,Q}^{K_{\text{ct}}+1}$

1:  $\text{OUT} \leftarrow \mathbf{bCT}_1 + \mathbf{bCT}_2 - (0, \dots, 0, \mathbf{bb})$

2: **for**  $i \in [K_{\text{ct}}]$ ,  $j \leq i$  **do**

3:   Set  $k = \theta(i, j)$  and set  $\gamma_k = 1/2$  if  $i = j$ ,  $\gamma_k = 1$  otherwise.

4:    $v(X) = G_{\text{crt}}^{-1} \left( \gamma_k (a_i \mathbf{a}_j + a_j \mathbf{a}_i) \right)$

5:    $\text{OUT} += \sum_x v_x(X) \text{Ten}_{k,x}$

6: **end for**

7: **return**  $\text{OUT}$

---

*Proof.* Let  $\text{OUT}$  be a results after running on line 1 of Algorithm 14. First we apply decryption of  $\text{OUT}$  as follows:

$$\begin{aligned}
&\varphi \left( \text{OUT} + \sum_{k,x} G_{\text{crt}}^{-1} \left( \gamma_k [a_j \mathbf{a}_i + a_i \mathbf{a}_j] \right)_x \text{Ten}_{k,x} \right) \\
&= \varphi(\text{CT}_1) \varphi(\text{CT}_2) + \sum_{k,x} A''_{k,x}(X) sk_i(X) sk_j(X) \\
&\quad + \sum_{k,x} G_{\text{crt}}^{-1} \left( \gamma_k [a_j \mathbf{a}_i + a_i \mathbf{a}_j] \right)_x E''_{k,x}(X),
\end{aligned} \tag{17}$$

where  $A''_{k,x}$  are gadget errors,  $E''_{k,x}(X)$  are errors in  $\text{Ten}_{k,x}$ . However,  $\varphi(\text{CT}_1) \varphi(\text{CT}_2) - m_1(X)m_2(X)$  are calculated as follows:

$$m_1(X) \mathcal{E}_{\text{pack},2}(X) + m_2(X) \mathcal{E}_{\text{pack},1}(X) + \mathcal{E}_{\text{pack},1}(X) \mathcal{E}_{\text{pack},2}(X), \tag{18}$$

where  $\mathcal{E}_{\text{pack},1}(X)$  and  $\mathcal{E}_{\text{pack},2}(X)$  are packing error of  $\text{CT}_1$  and  $\text{CT}_2$ , respectively. Without loss of generality, we analyze a worst-case error of  $\alpha = p-1$ -th coefficient having messages  $m(X) = \mathbf{m}(X) = \sum_{i \in [p]} \Delta \beta X^i$ . Since  $|\mathcal{E}_{\text{pack},1}(X)\mathcal{E}_{\text{pack},2}(X)| = O(n |\mathcal{E}_{\text{pack},1}^{(p-1)}|^2)$ , hence from (15) and (16), and by using the fact  $\Delta = \Omega(n|\mathcal{E}_{\text{pack}}|)$ , (18) is bounded as  $O(\Delta p \beta |\mathcal{E}_{\text{pack}}^{(p-1)}|)$ . Moreover for (17), the second summation is bounded as  $O(K_{\text{ct}}^2 n^2 l_{\text{ten}} B_{\text{ten}})$ , and the third summation is bounded as  $O(\sigma B_{\text{ten}} K_{\text{gct}} \sqrt{l_{\text{ten}} N_{\text{gct}}})$ , by using Corollary 2.  $\square$

### Proof of Lemma 7

*Proof.* Since total scalar multiplying CT is  $2^{c+\log N_{\text{gct}}+1-q}/Q_1 \nu 2^{\eta_1+s+c+1+f-q}$ , error in  $\mathbf{ct}$  is multiplied by those scalar as in first term of (13). When Algorithm 3 runs on Line 1,  $O(\sqrt{(K_{\text{ct}}n+1)t})$ -bounded floor errors are added, which is negligible compared to  $|\mathcal{E}_{\text{ten}}^{(p-1)}|/\Delta$ .

Next, we consider CT in Line 1 as a ciphertext modulo  $\nu 2^{\eta_0}$ . If the modulus  $Q_0 = \nu 2^{\eta_0} + 1$  of CT is changed to  $\nu 2^{\eta_0}$ , then  $O(\sqrt{N_{\text{gct}} K_{\text{gct}}})$  errors are added by following decryption equation on  $\mathbb{Z}$ :

$$b - a_i s_i = m + e + \bar{h} Q_0 = m + e + \bar{h} + \bar{h} \nu 2^{\eta_0} \in \mathbb{Z}$$

, for some  $\bar{h} \in \mathbb{Z}$  where  $\bar{h} = O(\sqrt{N_{\text{gct}} K_{\text{gct}}})$  for ternary secret key [11], which is negligible. Moreover, we regard the message  $m Q_1 = m \nu 2^{\eta_1} + m \nu$  as a message  $m \nu 2^{\eta_0}$  with error  $m \nu$ . Therefore, the message **out** is  $(m_{f+s} \dots m_f)_{(2)} 2^{\log N_{\text{gct}} - s}$  after rounding all in Algorithm 3, and added error  $\nu m$  which has a maximum value  $\nu p(\beta - 1)^2$ , becomes the rest first term of (13).

After rounding on Line 3,  $O(\sqrt{n K_{\text{ct}}})$ -bounded rounding error is added and  $O(\sqrt{n K_{\text{ct}} t})$ -bounded key-switching error is added. Both errors are divided by  $2^{q-1-\log N_{\text{gct}}}$ , after running Line 9, which is second term in (13).

Finally, rounding error after running on Line 10 in Algorithm 3 are added. However, we use  $h$ -sparse secret key for encrypting KS and only a number of  $h$  rounding errors are added. By using subgaussian property with Corollary 2, this error is  $O(\sigma \sqrt{ht})$  bounded, hence third term of (13) holds.  $\square$